



Szczegółowe tabele doboru pomp ciepła

SOLIS

Temperatura zasilania źródła dolnego

6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21

Moc chłodnicza kW

Temperatura zasilania	41	2.9	3.0	3.2	3.3	3.5	3.6	3.8	3.9	4.1	4.2	4.4	4.6	4.7	4.9	5.1	5.3
	43	2.8	3.0	3.1	3.2	3.4	3.5	3.7	3.8	4.0	4.1	4.3	4.5	4.6	4.8	5.0	5.2
	45	2.8	2.9	3.0	3.2	3.3	3.4	3.6	3.7	3.9	4.0	4.2	4.4	4.5	4.7	4.9	5.1
	47	2.7	2.8	2.9	3.1	3.2	3.4	3.5	3.6	3.8	3.9	4.1	4.3	4.4	4.6	4.8	5.0
	49	2.6	2.7	2.8	3.0	3.1	3.3	3.4	3.5	3.7	3.8	4.0	4.2	4.3	4.5	4.7	4.8
	51	2.5	2.6	2.8	2.9	3.0	3.2	3.3	3.5	3.6	3.7	3.9	4.0	4.2	4.4	4.5	4.7
	53	2.5	2.6	2.7	2.8	3.0	3.1	3.2	3.4	3.5	3.6	3.8	3.9	4.1	4.3	4.4	4.6
	55	2.4	2.5	2.6	2.7	2.8	3.0	3.1	3.3	3.4	3.5	3.7	3.8	4.0	4.1	4.3	4.5
	57	2.3	2.4	2.5	2.6	2.8	2.9	3.0	3.2	3.3	3.4	3.6	3.7	3.9	4.0	4.2	4.3
	59	2.2	2.3	2.4	2.5	2.7	2.8	2.9	3.1	3.2	3.3	3.5	3.6	3.8	3.9	4.1	4.2
	61	2.1	2.2	2.3	2.4	2.6	2.7	2.8	3.0	3.1	3.2	3.4	3.5	3.6	3.8	3.9	4.1
	63	2.0	2.1	2.2	2.4	2.5	2.6	2.7	2.8	3.0	3.1	3.2	3.4	3.5	3.7	3.8	4.0
	65	1.9	2.0	2.1	2.3	2.4	2.5	2.6	2.7	2.8	3.0	3.1	3.3	3.4	3.5	3.7	3.8
	67	1.8	1.9	2.0	2.1	2.3	2.4	2.5	2.6	2.7	2.9	3.0	3.1	3.3	3.4	3.6	3.7
	69	1.7	1.8	1.9	2.0	2.1	2.3	2.4	2.5	2.6	2.7	2.9	3.0	3.1	3.3	3.4	3.6
	71		1.7	1.8	1.9	2.0	2.1	2.3	2.4	2.5	2.6	2.7	2.9	3.0	3.1	3.3	3.4
73				1.8	1.9	2.0	2.1	2.2	2.4	2.5	2.6	2.7	2.9	3.0	3.1	3.3	
75						1.9	2.0	2.1	2.2	2.3	2.5	2.6	2.7	2.8	3.0	3.1	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.8
	43	1.0	1.0	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
	45	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	0.9	0.9
	47	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
	49	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.0
	51	1.2	1.2	1.2	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	53	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	55	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	57	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
	59	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.3	1.3
	61	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4
	63	1.6	1.6	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
	65	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.5
	67	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.6	1.6	1.6	1.6	1.6
	69	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7
	71		1.9	1.9	1.9	1.9	1.9	1.9	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8
73				2.0	2.0	2.0	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	
75						2.1	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	

Moc grzewcza (kW)

Temperatura zasilania	41	3.7	3.9	4.0	4.1	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.9	6.1
	43	3.7	3.8	4.0	4.1	4.2	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.5	5.6	5.8	6.0
	45	3.7	3.8	3.9	4.1	4.2	4.3	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.6	5.7	5.9
	47	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.8
	49	3.6	3.8	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.4	5.6	5.8
	51	3.6	3.7	3.8	4.0	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.5	5.7
	53	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.6
	55	3.6	3.7	3.8	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.4	5.6
	57	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.0	5.2	5.3	5.5
	59	3.5	3.6	3.7	3.9	4.0	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.0	5.1	5.3	5.4
	61	3.5	3.6	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.5	4.7	4.8	4.9	5.1	5.2	5.4
	63	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.7	4.9	5.0	5.2	5.3
	65	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.6	4.7	4.8	5.0	5.1	5.2
	67	3.5	3.6	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.4	4.5	4.6	4.8	4.9	5.0	5.2
	69	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.7	4.9	5.0	5.1
	71		3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.6	4.7	4.8	4.9	5.1
73				3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5	4.6	4.7	4.9	5.0	
75						3.8	3.9	4.0	4.1	4.2	4.3	4.5	4.6	4.7	4.8	4.9	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.1	4.3	4.4	4.6	4.8	4.9	5.1	5.3	5.5	5.8	5.9	6.1	6.4	6.6	6.9	7.2
	43	3.9	4.0	4.2	4.3	4.5	4.7	4.8	5.0	5.2	5.4	5.5	5.8	6.0	6.2	6.4	6.7
	45	3.7	3.8	3.9	4.1	4.2	4.4	4.5	4.7	4.9	5.1	5.3	5.4	5.6	5.8	6.1	6.3
	47	3.5	3.6	3.8	3.9	4.0	4.1	4.3	4.5	4.6	4.8	5.0	5.1	5.3	5.5	5.7	5.9
	49	3.3	3.4	3.5	3.6	3.8	3.9	4.0	4.2	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.5
	51	3.1	3.2	3.3	3.5	3.6	3.7	3.9	3.9	4.1	4.2	4.4	4.6	4.7	4.9	5.0	5.2
	53	2.9	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.9	4.0	4.2	4.3	4.4	4.6	4.7	4.9
	55	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.8	3.9	4.0	4.2	4.3	4.5	4.6
	57	2.7	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.7	3.8	3.9	4.0	4.1	4.3
	59	2.5	2.6	2.6	2.8	2.8	2.9	3.0	3.1	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.1
	61	2.4	2.5	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8
	63	2.2	2.3	2.4	2.4	2.6	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6
	65	2.1	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4
	67	2.0	2.1	2.1	2.2	2.3	2.4	2.4	2.5	2.6	2.7	2.7	2.8	2.9	3.0	3.1	3.2
	69	1.9	1.9	2.0	2.1	2.2	2.2	2.3	2.3	2.4	2.5	2.6	2.7	2.7	2.8	2.9	3.0
	71		1.9	1.9	2.0	2.0	2.1	2.1	2.2	2.3	2.4	2.4	2.5	2.6	2.7	2.7	2.8
73				1.9	1.9	2.0	2.0	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.7	
75						1.9	1.9	2.0	2.0	2.1	2.2	2.2	2.3	2.4	2.5	2.5	

Temperatura zasilania źródła dolnego

6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	3.8	4.0	4.2	4.3	4.5	4.7	4.9	5.1	5.3	5.5	5.7	5.9	6.2	6.4	6.6	6.9
	43	3.7	3.9	4.1	4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.6	5.8	6.0	6.2	6.5	6.7
	45	3.6	3.8	4.0	4.1	4.3	4.5	4.7	4.9	5.1	5.3	5.5	5.7	5.9	6.1	6.3	6.5
	47	3.5	3.7	3.9	4.0	4.2	4.4	4.6	4.8	4.9	5.1	5.3	5.5	5.8	6.0	6.2	6.4
	49	3.4	3.6	3.8	3.9	4.1	4.3	4.5	4.6	4.8	5.0	5.2	5.4	5.6	5.8	6.0	6.2
	51	3.3	3.5	3.7	3.8	4.0	4.2	4.3	4.5	4.7	4.9	5.1	5.3	5.5	5.7	5.9	6.1
	53	3.3	3.4	3.6	3.7	3.9	4.0	4.2	4.4	4.6	4.8	4.9	5.1	5.3	5.5	5.7	5.9
	55	3.2	3.3	3.5	3.6	3.8	3.9	4.1	4.3	4.5	4.6	4.8	5.0	5.2	5.4	5.6	5.8
	57	3.1	3.2	3.4	3.5	3.7	3.8	4.0	4.2	4.3	4.5	4.7	4.9	5.1	5.2	5.4	5.6
	59	3.0	3.1	3.2	3.4	3.6	3.7	3.9	4.0	4.2	4.4	4.6	4.7	4.9	5.1	5.3	5.5
	61	2.8	3.0	3.1	3.3	3.4	3.6	3.7	3.9	4.1	4.2	4.4	4.6	4.8	5.0	5.1	5.3
	63	2.7	2.9	3.0	3.2	3.3	3.5	3.6	3.8	3.9	4.1	4.3	4.5	4.6	4.8	5.0	5.2
	65	2.6	2.8	2.9	3.1	3.2	3.4	3.5	3.7	3.8	4.0	4.1	4.3	4.5	4.7	4.8	5.0
	67	2.5	2.7	2.8	2.9	3.1	3.2	3.4	3.5	3.7	3.8	4.0	4.2	4.3	4.5	4.7	4.9
	69	2.4	2.5	2.7	2.8	3.0	3.1	3.2	3.4	3.5	3.7	3.9	4.0	4.2	4.3	4.5	4.7
	71		2.4	2.5	2.7	2.8	3.0	3.1	3.3	3.4	3.6	3.7	3.9	4.0	4.2	4.4	4.5
73				2.6	2.7	2.8	3.0	3.1	3.3	3.4	3.6	3.7	3.9	4.0	4.2	4.3	
75						2.7	2.8	3.0	3.1	3.3	3.4	3.5	3.7	3.9	4.0	4.2	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
	43	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
	45	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
	47	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
	49	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4
	51	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.4	1.4	1.4	1.4	1.4	1.4	1.4
	53	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
	55	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6
	57	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.6	1.6	1.6
	59	1.8	1.8	1.8	1.8	1.8	1.8	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7
	61	1.9	1.9	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8
	63	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
	65	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
	67	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.0
	69	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.1	2.1
	71		2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.2	2.2
73				2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.3	
75						2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.4	

Moc grzewcza (kW)

Temperatura zasilania	41	4.9	5.0	5.2	5.4	5.6	5.8	5.9	6.1	6.3	6.5	6.8	7.0	7.2	7.4	7.6	7.9
	43	4.8	5.0	5.2	5.3	5.5	5.7	5.9	6.1	6.3	6.5	6.7	6.9	7.1	7.3	7.5	7.8
	45	4.8	5.0	5.1	5.3	5.5	5.6	5.8	6.0	6.2	6.4	6.6	6.8	7.0	7.2	7.4	7.7
	47	4.8	4.9	5.1	5.2	5.4	5.6	5.8	6.0	6.1	6.3	6.5	6.7	6.9	7.1	7.4	7.6
	49	4.7	4.9	5.0	5.2	5.4	5.5	5.7	5.9	6.1	6.3	6.5	6.7	6.9	7.1	7.3	7.5
	51	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.8	6.0	6.2	6.4	6.6	6.8	7.0	7.2	7.4
	53	4.7	4.8	5.0	5.1	5.3	5.4	5.6	5.8	6.0	6.1	6.3	6.5	6.7	6.9	7.1	7.3
	55	4.6	4.8	4.9	5.1	5.2	5.4	5.6	5.7	5.9	6.1	6.3	6.4	6.6	6.8	7.0	7.2
	57	4.6	4.8	4.9	5.1	5.2	5.4	5.5	5.7	5.9	6.0	6.2	6.4	6.6	6.7	6.9	7.1
	59	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.6	5.8	6.0	6.1	6.3	6.5	6.7	6.9	7.0
	61	4.6	4.7	4.8	5.0	5.1	5.3	5.4	5.6	5.7	5.9	6.1	6.2	6.4	6.6	6.8	7.0
	63	4.6	4.7	4.8	5.0	5.1	5.2	5.4	5.5	5.7	5.9	6.0	6.2	6.3	6.5	6.7	6.9
	65	4.5	4.7	4.8	4.9	5.1	5.2	5.3	5.5	5.6	5.8	6.0	6.1	6.3	6.5	6.6	6.8
	67	4.5	4.7	4.8	4.9	5.0	5.2	5.3	5.5	5.6	5.7	5.9	6.1	6.2	6.4	6.5	6.7
	69	4.5	4.6	4.8	4.9	5.0	5.1	5.3	5.4	5.6	5.7	5.8	6.0	6.2	6.3	6.5	6.6
	71		4.6	4.7	4.9	5.0	5.1	5.2	5.4	5.5	5.7	5.8	5.9	6.1	6.2	6.4	6.6
73				4.8	5.0	5.1	5.2	5.3	5.5	5.6	5.7	5.9	6.0	6.2	6.3	6.5	
75						5.1	5.2	5.3	5.4	5.6	5.7	5.8	6.0	6.1	6.3	6.4	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.2	4.3	4.5	4.7	4.8	5.0	5.1	5.3	5.5	5.7	5.9	6.1	6.3	6.5	6.7	6.9
	43	3.9	4.1	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.4	5.5	5.7	5.9	6.1	6.3	6.5
	45	3.7	3.9	4.0	4.1	4.3	4.4	4.6	4.8	4.9	5.1	5.2	5.4	5.6	5.8	5.9	6.1
	47	3.5	3.7	3.8	3.9	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.1	5.3	5.4	5.6	5.8
	49	3.4	3.5	3.6	3.7	3.9	4.0	4.1	4.2	4.4	4.5	4.7	4.8	5.0	5.2	5.3	5.4
	51	3.2	3.3	3.4	3.5	3.6	3.7	3.9	4.0	4.1	4.3	4.4	4.6	4.7	4.8	5.0	5.1
	53	3.0	3.1	3.2	3.3	3.4	3.6	3.7	3.8	3.9	4.0	4.2	4.3	4.5	4.6	4.7	4.9
	55	2.9	3.0	3.0	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.5	4.6
	57	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.9	4.0	4.1	4.2	4.3
	59	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.7	3.8	3.9	4.0	4.1
	61	2.5	2.5	2.6	2.7	2.8	2.9	3.0	3.1	3.1	3.3	3.3	3.4	3.6	3.7	3.8	3.9
	63	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7
	65	2.2	2.3	2.4	2.4	2.5	2.6	2.7	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5
	67	2.1	2.2	2.2	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3
	69	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.1
	71		2.0	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.9	2.9
73				2.0	2.1	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	
75						2.0	2.0	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.6	

Temperatura zasilania źródła dolnego

6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	4.5	4.7	4.9	5.1	5.3	5.5	5.7	6.0	6.2	6.5	6.7	7.0	7.2	7.5	7.8	8.1
	43	4.4	4.6	4.8	5.0	5.2	5.4	5.6	5.8	6.1	6.3	6.6	6.8	7.1	7.3	7.6	7.9
	45	4.3	4.5	4.6	4.8	5.1	5.3	5.5	5.7	5.9	6.2	6.4	6.7	6.9	7.2	7.4	7.7
	47	4.2	4.3	4.5	4.7	4.9	5.1	5.3	5.6	5.8	6.0	6.3	6.5	6.8	7.0	7.3	7.6
	49	4.1	4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.6	5.9	6.1	6.3	6.6	6.8	7.1	7.4
	51	3.9	4.1	4.3	4.5	4.7	4.9	5.1	5.3	5.5	5.7	6.0	6.2	6.4	6.7	6.9	7.2
	53	3.8	4.0	4.2	4.4	4.5	4.7	4.9	5.1	5.4	5.6	5.8	6.0	6.3	6.5	6.8	7.0
	55	3.7	3.9	4.1	4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.6	5.9	6.1	6.3	6.6	6.8
	57	3.6	3.8	3.9	4.1	4.3	4.5	4.7	4.9	5.1	5.3	5.5	5.7	5.9	6.2	6.4	6.7
	59	3.5	3.6	3.8	4.0	4.2	4.3	4.5	4.7	4.9	5.1	5.3	5.5	5.8	6.0	6.2	6.5
	61	3.4	3.5	3.7	3.9	4.0	4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.6	5.8	6.0	6.3
	63	3.3	3.4	3.6	3.7	3.9	4.1	4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.6	5.9	6.1
	65	3.1	3.3	3.4	3.6	3.8	3.9	4.1	4.3	4.5	4.6	4.8	5.0	5.2	5.5	5.7	5.9
	67	3.0	3.2	3.3	3.5	3.6	3.8	3.9	4.1	4.3	4.5	4.7	4.9	5.1	5.3	5.5	5.7
	69	2.9	3.0	3.2	3.3	3.5	3.6	3.8	4.0	4.1	4.3	4.5	4.7	4.9	5.1	5.3	5.5
	71		2.9	3.0	3.2	3.3	3.5	3.6	3.8	4.0	4.2	4.3	4.5	4.7	4.9	5.1	5.3
73				3.0	3.2	3.3	3.5	3.7	3.8	4.0	4.2	4.3	4.5	4.7	4.9	5.1	
75						3.2	3.3	3.5	3.7	3.8	4.0	4.2	4.3	4.5	4.7	4.9	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	1.4	1.4	1.4	1.4	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
	43	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4	1.4
	45	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.4	1.4	1.4
	47	1.6	1.6	1.6	1.6	1.6	1.6	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
	49	1.7	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6
	51	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7
	53	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.7	1.7
	55	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.8	1.8	1.8	1.8	1.8	1.8
	57	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
	59	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
	61	2.2	2.2	2.2	2.2	2.2	2.2	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1
	63	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2
	65	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3
	67	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.4	2.4	2.4	2.4	2.4	2.4
	69	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.5	2.5	2.5
	71		2.8	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.6
73				2.9	2.9	2.9	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	
75						3.0	3.0	3.0	3.0	3.0	2.9	2.9	2.9	2.9	2.9	2.9	

Moc grzewcza (kW)

Temperatura zasilania	41	5.7	5.9	6.1	6.3	6.5	6.7	6.9	7.2	7.4	7.6	7.9	8.1	8.4	8.7	8.9	9.2
	43	5.7	5.9	6.1	6.3	6.5	6.7	6.9	7.1	7.3	7.6	7.8	8.1	8.3	8.6	8.8	9.1
	45	5.6	5.8	6.0	6.2	6.4	6.6	6.8	7.0	7.3	7.5	7.7	8.0	8.2	8.5	8.7	9.0
	47	5.6	5.8	6.0	6.2	6.3	6.5	6.7	7.0	7.2	7.4	7.6	7.9	8.1	8.4	8.6	8.9
	49	5.6	5.7	5.9	6.1	6.3	6.5	6.7	6.9	7.1	7.3	7.6	7.8	8.0	8.3	8.5	8.8
	51	5.5	5.7	5.9	6.1	6.2	6.4	6.6	6.8	7.0	7.3	7.5	7.7	7.9	8.2	8.4	8.7
	53	5.5	5.7	5.8	6.0	6.2	6.4	6.6	6.8	7.0	7.2	7.4	7.6	7.9	8.1	8.3	8.6
	55	5.5	5.6	5.8	6.0	6.1	6.3	6.5	6.7	6.9	7.1	7.3	7.5	7.8	8.0	8.2	8.5
	57	5.4	5.6	5.8	5.9	6.1	6.3	6.5	6.6	6.8	7.0	7.2	7.5	7.7	7.9	8.1	8.4
	59	5.4	5.6	5.7	5.9	6.1	6.2	6.4	6.6	6.8	7.0	7.2	7.4	7.6	7.8	8.1	8.3
	61	5.4	5.5	5.7	5.9	6.0	6.2	6.4	6.5	6.7	6.9	7.1	7.3	7.5	7.7	8.0	8.2
	63	5.4	5.5	5.7	5.8	6.0	6.1	6.3	6.5	6.7	6.8	7.0	7.2	7.4	7.7	7.9	8.1
	65	5.4	5.5	5.6	5.8	5.9	6.1	6.3	6.4	6.6	6.8	7.0	7.2	7.4	7.6	7.8	8.0
	67	5.4	5.5	5.6	5.8	5.9	6.1	6.2	6.4	6.6	6.7	6.9	7.1	7.3	7.5	7.7	7.9
	69	5.3	5.5	5.6	5.7	5.9	6.0	6.2	6.3	6.5	6.7	6.9	7.0	7.2	7.4	7.6	7.8
	71		5.5	5.6	5.7	5.9	6.0	6.2	6.3	6.5	6.6	6.8	7.0	7.2	7.3	7.5	7.7
73				5.7	5.8	6.0	6.1	6.3	6.4	6.6	6.7	6.9	7.1	7.3	7.5	7.7	
75						6.0	6.1	6.2	6.4	6.5	6.7	6.9	7.0	7.2	7.4	7.6	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.2	4.3	4.5	4.7	4.9	5.0	5.2	5.4	5.6	5.8	6.0	6.2	6.4	6.6	6.8	7.1
	43	4.0	4.1	4.3	4.4	4.6	4.8	4.9	5.1	5.3	5.4	5.7	5.8	6.0	6.2	6.4	6.6
	45	3.7	3.9	4.0	4.2	4.3	4.5	4.6	4.8	5.0	5.1	5.3	5.5	5.7	5.9	6.0	6.3
	47	3.6	3.7	3.8	3.9	4.1	4.2	4.4	4.5	4.7	4.8	5.0	5.2	5.3	5.5	5.7	5.9
	49	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.4	5.6
	51	3.2	3.3	3.4	3.5	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.6	4.7	4.9	5.1	5.2
	53	3.0	3.1	3.2	3.4	3.4	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.5	4.6	4.8	4.9
	55	2.9	3.0	3.0	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.4	4.5	4.6
	57	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.9	4.0	4.1	4.2	4.4
	59	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.8	3.9	4.0	4.1
	61	2.5	2.5	2.6	2.7	2.8	2.9	3.0	3.0	3.2	3.2	3.4	3.4	3.6	3.7	3.8	3.9
	63	2.3	2.4	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.2	3.4	3.5	3.6	3.7
	65	2.2	2.3	2.3	2.4	2.5	2.6	2.7	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5
	67	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.7	2.7	2.8	2.9	3.0	3.1	3.2	3.3
	69	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.4	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1
	71		2.0	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.9
73				2.0	2.0	2.1	2.2	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.8	
75						2.0	2.0	2.1	2.2	2.2	2.3	2.3	2.4	2.5	2.5	2.6	

Pompa ciepła typ:

SO-100H

Temperatura zasilania źródła dolnego

6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	5.2	5.4	5.7	5.9	6.1	6.4	6.6	6.9	7.2	7.5	7.7	8.0	8.3	8.6	8.9	9.3
	43	5.1	5.3	5.5	5.8	6.0	6.2	6.5	6.8	7.0	7.3	7.6	7.9	8.2	8.5	8.8	9.1
	45	4.9	5.2	5.4	5.6	5.9	6.1	6.4	6.6	6.9	7.2	7.4	7.7	8.0	8.3	8.6	8.9
	47	4.8	5.0	5.3	5.5	5.7	6.0	6.2	6.5	6.7	7.0	7.3	7.5	7.8	8.1	8.4	8.7
	49	4.7	4.9	5.1	5.3	5.6	5.8	6.1	6.3	6.6	6.8	7.1	7.4	7.7	8.0	8.2	8.6
	51	4.6	4.8	5.0	5.2	5.4	5.7	5.9	6.2	6.4	6.7	6.9	7.2	7.5	7.8	8.1	8.4
	53	4.4	4.6	4.8	5.1	5.3	5.5	5.8	6.0	6.2	6.5	6.8	7.0	7.3	7.6	7.9	8.2
	55	4.3	4.5	4.7	4.9	5.1	5.4	5.6	5.8	6.1	6.3	6.6	6.9	7.1	7.4	7.7	8.0
	57	4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.7	5.9	6.2	6.4	6.7	6.9	7.2	7.5	7.8
	59	4.0	4.2	4.4	4.6	4.8	5.0	5.3	5.5	5.7	6.0	6.2	6.5	6.8	7.0	7.3	7.6
	61	3.9	4.1	4.3	4.5	4.7	4.9	5.1	5.3	5.6	5.8	6.0	6.3	6.6	6.8	7.1	7.4
	63	3.7	3.9	4.1	4.3	4.5	4.7	4.9	5.1	5.4	5.6	5.9	6.1	6.4	6.6	6.9	7.1
	65	3.6	3.8	3.9	4.1	4.3	4.5	4.7	5.0	5.2	5.4	5.7	5.9	6.1	6.4	6.7	6.9
	67	3.4	3.6	3.8	4.0	4.2	4.4	4.6	4.8	5.0	5.2	5.4	5.7	5.9	6.2	6.4	6.7
	69	3.3	3.4	3.6	3.8	4.0	4.2	4.4	4.6	4.8	5.0	5.2	5.5	5.7	6.0	6.2	6.5
	71		3.3	3.4	3.6	3.8	4.0	4.2	4.4	4.6	4.8	5.0	5.2	5.5	5.7	6.0	6.2
73				3.4	3.6	3.8	4.0	4.2	4.4	4.6	4.8	5.0	5.2	5.5	5.7	6.0	
75						3.6	3.8	4.0	4.2	4.4	4.6	4.8	5.0	5.2	5.5	5.7	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5
	43	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6
	45	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7
	47	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8
	49	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.8	1.8	1.8	1.8	1.8	1.8	1.8	1.8
	51	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
	53	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
	55	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1
	57	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2
	59	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3
	61	2.5	2.5	2.5	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
	63	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.5	2.5	2.5	2.5	2.5	2.5	2.5
	65	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7
	67	2.9	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
	69	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9
	71		3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
73				3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.2	3.2	3.2	3.2	3.2	3.2	
75						3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	

Moc grzewcza (kW)

Temperatura zasilania	41	6.6	6.8	7.1	7.3	7.5	7.8	8.0	8.3	8.6	8.8	9.1	9.4	9.7	10.0	10.3	10.6
	43	6.5	6.8	7.0	7.2	7.5	7.7	8.0	8.2	8.5	8.8	9.0	9.3	9.6	9.9	10.2	10.5
	45	6.5	6.7	6.9	7.2	7.4	7.6	7.9	8.1	8.4	8.7	8.9	9.2	9.5	9.8	10.1	10.4
	47	6.4	6.7	6.9	7.1	7.3	7.6	7.8	8.1	8.3	8.6	8.9	9.1	9.4	9.7	10.0	10.3
	49	6.4	6.6	6.8	7.0	7.3	7.5	7.7	8.0	8.3	8.5	8.8	9.1	9.3	9.6	9.9	10.2
	51	6.3	6.6	6.8	7.0	7.2	7.4	7.7	7.9	8.2	8.4	8.7	9.0	9.2	9.5	9.8	10.1
	53	6.3	6.5	6.7	6.9	7.1	7.4	7.6	7.8	8.1	8.3	8.6	8.9	9.1	9.4	9.7	10.0
	55	6.3	6.5	6.7	6.9	7.1	7.3	7.5	7.8	8.0	8.3	8.5	8.8	9.0	9.3	9.6	9.9
	57	6.2	6.4	6.6	6.8	7.0	7.2	7.5	7.7	7.9	8.2	8.4	8.7	9.0	9.2	9.5	9.8
	59	6.2	6.4	6.6	6.8	7.0	7.2	7.4	7.6	7.9	8.1	8.4	8.6	8.9	9.1	9.4	9.7
	61	6.2	6.3	6.5	6.7	6.9	7.1	7.3	7.6	7.8	8.0	8.3	8.5	8.8	9.0	9.3	9.6
	63	6.1	6.3	6.5	6.7	6.9	7.1	7.3	7.5	7.7	7.9	8.2	8.4	8.7	8.9	9.2	9.5
	65	6.1	6.3	6.4	6.6	6.8	7.0	7.2	7.4	7.6	7.9	8.1	8.3	8.6	8.8	9.1	9.4
	67	6.1	6.2	6.4	6.6	6.8	7.0	7.2	7.4	7.6	7.8	8.0	8.3	8.5	8.7	9.0	9.2
	69	6.0	6.2	6.4	6.5	6.7	6.9	7.1	7.3	7.5	7.7	7.9	8.2	8.4	8.6	8.9	9.1
	71		6.2	6.3	6.5	6.7	6.9	7.1	7.2	7.4	7.7	7.9	8.1	8.3	8.5	8.8	9.0
73				6.5	6.7	6.8	7.0	7.2	7.4	7.6	7.8	8.0	8.2	8.5	8.7	8.9	
75						6.8	7.0	7.1	7.3	7.5	7.7	7.9	8.1	8.4	8.6	8.8	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.3	4.4	4.6	4.7	4.9	5.1	5.2	5.4	5.6	5.8	6.0	6.1	6.3	6.6	6.8	7.0
	43	4.0	4.2	4.3	4.5	4.6	4.8	4.9	5.1	5.3	5.4	5.6	5.8	6.0	6.2	6.4	6.6
	45	3.8	4.0	4.1	4.2	4.4	4.5	4.7	4.8	5.0	5.2	5.3	5.5	5.7	5.8	6.0	6.2
	47	3.6	3.8	3.9	4.0	4.1	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.9
	49	3.4	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.5
	51	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.1	5.3
	53	3.1	3.2	3.3	3.4	3.5	3.6	3.8	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	5.0
	55	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.6	4.7
	57	2.8	2.9	3.0	3.1	3.2	3.2	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4
	59	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2
	61	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0
	63	2.4	2.4	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7
	65	2.2	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.5
	67	2.1	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3
	69	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.1
	71		2.0	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.5	2.6	2.6	2.7	2.8	2.9	2.9
73				2.0	2.0	2.1	2.2	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.8	
75						2.0	2.0	2.1	2.1	2.2	2.3	2.3	2.4	2.5	2.5	2.6	

Pompa ciepła typ:

SO-130H

Temperatura zasilania źródła dolnego

6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	6.3	6.6	6.9	7.1	7.4	7.8	8.1	8.4	8.7	9.1	9.4	9.8	10.2	10.6	11.0	11.4
	43	6.2	6.4	6.7	7.0	7.3	7.6	7.9	8.2	8.5	8.9	9.2	9.6	9.9	10.3	10.7	11.1
	45	6.0	6.3	6.5	6.8	7.1	7.4	7.7	8.0	8.3	8.7	9.0	9.3	9.7	10.1	10.5	10.9
	47	5.8	6.1	6.3	6.6	6.9	7.2	7.5	7.8	8.1	8.4	8.8	9.1	9.5	9.8	10.2	10.6
	49	5.7	5.9	6.2	6.4	6.7	7.0	7.3	7.6	7.9	8.2	8.5	8.9	9.2	9.6	10.0	10.3
	51	5.5	5.7	6.0	6.3	6.5	6.8	7.1	7.4	7.7	8.0	8.3	8.6	9.0	9.3	9.7	10.1
	53	5.3	5.6	5.8	6.1	6.3	6.6	6.9	7.2	7.5	7.8	8.1	8.4	8.7	9.1	9.4	9.8
	55	5.2	5.4	5.6	5.9	6.1	6.4	6.7	7.0	7.2	7.5	7.9	8.2	8.5	8.8	9.2	9.5
	57	5.0	5.2	5.4	5.7	5.9	6.2	6.5	6.7	7.0	7.3	7.6	7.9	8.2	8.6	8.9	9.3
	59	4.8	5.0	5.3	5.5	5.7	6.0	6.3	6.5	6.8	7.1	7.4	7.7	8.0	8.3	8.6	9.0
	61	4.6	4.8	5.1	5.3	5.5	5.8	6.0	6.3	6.6	6.9	7.1	7.4	7.7	8.1	8.4	8.7
	63	4.4	4.7	4.9	5.1	5.3	5.6	5.8	6.1	6.3	6.6	6.9	7.2	7.5	7.8	8.1	8.4
	65	4.3	4.5	4.7	4.9	5.1	5.4	5.6	5.9	6.1	6.4	6.7	6.9	7.2	7.5	7.8	8.1
	67	4.1	4.3	4.5	4.7	4.9	5.2	5.4	5.6	5.9	6.1	6.4	6.7	7.0	7.3	7.6	7.9
	69	3.9	4.1	4.3	4.5	4.7	4.9	5.2	5.4	5.7	5.9	6.2	6.4	6.7	7.0	7.3	7.6
	71		3.9	4.1	4.3	4.5	4.7	4.9	5.2	5.4	5.7	5.9	6.2	6.4	6.7	7.0	7.3
73				4.1	4.3	4.5	4.7	4.9	5.2	5.4	5.7	5.9	6.2	6.4	6.7	7.0	
75						4.3	4.5	4.7	4.9	5.2	5.4	5.6	5.9	6.2	6.4	6.7	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9
	43	1.9	1.9	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0
	45	2.0	2.0	2.0	2.0	2.0	2.0	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1
	47	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.1	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2
	49	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.3	2.3	2.3	2.3	2.3	2.3	2.3
	51	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
	53	2.4	2.4	2.4	2.4	2.4	2.4	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
	55	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6
	57	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7
	59	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
	61	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
	63	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
	65	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
	67	3.5	3.5	3.5	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4
	69	3.7	3.7	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6
	71		3.9	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8
73				4.1	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	
75						4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	

Moc grzewcza (kW)

Temperatura zasilania	41	8.0	8.3	8.6	8.8	9.1	9.4	9.8	10.1	10.4	10.8	11.1	11.5	11.9	12.2	12.6	13.0
	43	7.9	8.2	8.5	8.8	9.0	9.3	9.7	10.0	10.3	10.6	11.0	11.3	11.7	12.1	12.5	12.9
	45	7.9	8.1	8.4	8.7	8.9	9.2	9.5	9.9	10.2	10.5	10.9	11.2	11.6	11.9	12.3	12.7
	47	7.8	8.0	8.3	8.6	8.9	9.1	9.4	9.7	10.1	10.4	10.7	11.1	11.4	11.8	12.2	12.5
	49	7.7	8.0	8.2	8.5	8.8	9.0	9.3	9.6	9.9	10.3	10.6	10.9	11.3	11.6	12.0	12.4
	51	7.6	7.9	8.1	8.4	8.7	8.9	9.2	9.5	9.8	10.1	10.5	10.8	11.1	11.5	11.8	12.2
	53	7.6	7.8	8.1	8.3	8.6	8.8	9.1	9.4	9.7	10.0	10.3	10.7	11.0	11.3	11.7	12.1
	55	7.5	7.8	8.0	8.2	8.5	8.8	9.0	9.3	9.6	9.9	10.2	10.5	10.8	11.2	11.5	11.9
	57	7.5	7.7	7.9	8.2	8.4	8.7	8.9	9.2	9.5	9.8	10.1	10.4	10.7	11.0	11.4	11.7
	59	7.4	7.6	7.9	8.1	8.3	8.6	8.8	9.1	9.4	9.7	10.0	10.3	10.6	10.9	11.2	11.6
	61	7.4	7.6	7.8	8.0	8.3	8.5	8.8	9.0	9.3	9.6	9.9	10.1	10.5	10.8	11.1	11.4
	63	7.3	7.5	7.8	8.0	8.2	8.4	8.7	8.9	9.2	9.5	9.7	10.0	10.3	10.6	11.0	11.3
	65	7.3	7.5	7.7	7.9	8.2	8.4	8.6	8.9	9.1	9.4	9.7	9.9	10.2	10.5	10.8	11.1
	67	7.3	7.5	7.7	7.9	8.1	8.3	8.6	8.8	9.0	9.3	9.6	9.8	10.1	10.4	10.7	11.0
	69	7.3	7.5	7.7	7.9	8.1	8.3	8.5	8.7	9.0	9.2	9.5	9.7	10.0	10.3	10.6	10.9
	71		7.5	7.7	7.9	8.1	8.3	8.5	8.7	8.9	9.2	9.4	9.7	9.9	10.2	10.5	10.8
73				7.8	8.0	8.2	8.4	8.7	8.9	9.1	9.3	9.6	9.8	10.1	10.4	10.6	
75						8.2	8.4	8.6	8.8	9.1	9.3	9.5	9.8	10.0	10.3	10.5	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.4	5.6	5.8	5.9	6.1	6.3	6.5	6.7	7.0
	43	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.1	5.3	5.4	5.6	5.7	5.9	6.1	6.4	6.6
	45	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.8	5.0	5.1	5.3	5.4	5.6	5.8	6.0	6.2
	47	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.4	5.6	5.8
	49	3.5	3.6	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.6	4.7	4.8	5.0	5.1	5.3	5.5
	51	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.0	5.2
	53	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.4	4.6	4.7	4.9
	55	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.4	4.6
	57	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3
	59	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.9	3.9	4.1
	61	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.1	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8
	63	2.3	2.4	2.5	2.6	2.7	2.7	2.8	2.9	3.0	3.1	3.1	3.2	3.3	3.4	3.5	3.6
	65	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.1	3.1	3.2	3.3	3.4
	67	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2
	69	2.0	2.0	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0
	71		1.9	2.0	2.1	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.8
73				1.9	2.0	2.0	2.1	2.2	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	
75						1.9	2.0	2.0	2.1	2.2	2.2	2.3	2.3	2.4	2.5	2.5	

Temperatura zasilania źródła dolnego

6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	8.1	8.4	8.8	9.1	9.5	9.9	10.3	10.7	11.1	11.6	12.0	12.5	13.0	13.5	14.0	14.5
	43	7.9	8.2	8.6	8.9	9.3	9.7	10.1	10.5	10.9	11.3	11.8	12.2	12.7	13.2	13.7	14.2
	45	7.7	8.0	8.4	8.7	9.1	9.5	9.8	10.2	10.7	11.1	11.5	12.0	12.4	12.9	13.4	13.9
	47	7.5	7.8	8.2	8.5	8.9	9.2	9.6	10.0	10.4	10.8	11.3	11.7	12.2	12.6	13.1	13.6
	49	7.3	7.6	8.0	8.3	8.7	9.0	9.4	9.8	10.2	10.6	11.0	11.4	11.9	12.3	12.8	13.3
	51	7.1	7.4	7.8	8.1	8.4	8.8	9.2	9.5	9.9	10.3	10.7	11.1	11.6	12.0	12.5	13.0
	53	6.9	7.2	7.6	7.9	8.2	8.6	8.9	9.3	9.7	10.0	10.5	10.9	11.3	11.7	12.2	12.7
	55	6.8	7.0	7.4	7.7	8.0	8.3	8.7	9.0	9.4	9.8	10.2	10.6	11.0	11.4	11.9	12.3
	57	6.6	6.8	7.1	7.4	7.8	8.1	8.4	8.8	9.1	9.5	9.9	10.3	10.7	11.1	11.6	12.0
	59	6.4	6.6	6.9	7.2	7.5	7.9	8.2	8.5	8.9	9.2	9.6	10.0	10.4	10.8	11.3	11.7
	61	6.2	6.4	6.7	7.0	7.3	7.6	7.9	8.3	8.6	9.0	9.3	9.7	10.1	10.5	10.9	11.4
	63	5.9	6.2	6.5	6.8	7.1	7.4	7.7	8.0	8.3	8.7	9.1	9.4	9.8	10.2	10.6	11.0
	65	5.7	6.0	6.3	6.5	6.8	7.1	7.4	7.7	8.1	8.4	8.8	9.1	9.5	9.9	10.3	10.7
	67	5.5	5.8	6.0	6.3	6.6	6.9	7.2	7.5	7.8	8.1	8.5	8.8	9.2	9.6	9.9	10.3
	69	5.3	5.6	5.8	6.1	6.3	6.6	6.9	7.2	7.5	7.8	8.2	8.5	8.9	9.2	9.6	10.0
	71		5.3	5.6	5.8	6.1	6.4	6.6	6.9	7.2	7.5	7.9	8.2	8.5	8.9	9.3	9.6
73				5.6	5.8	6.1	6.4	6.6	6.9	7.2	7.5	7.9	8.2	8.5	8.9	9.3	
75						5.8	6.1	6.4	6.6	6.9	7.2	7.5	7.9	8.2	8.5	8.9	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	2.2	2.2	2.2	2.2	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	
	43	2.3	2.3	2.3	2.3	2.3	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
	45	2.4	2.4	2.4	2.4	2.4	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
	47	2.5	2.5	2.5	2.5	2.5	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6	2.6
	49	2.6	2.6	2.6	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7
	51	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.9
	53	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	3.0	3.0	3.0
	55	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.1	3.1	3.1	3.1	3.1	3.1	3.1
	57	3.1	3.1	3.1	3.1	3.1	3.1	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
	59	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.4
	61	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	63	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6
	65	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8
	67	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	4.0	4.0	4.0
	69	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1
	71		4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
73				4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	
75						4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	

Moc grzewcza (kW)

Temperatura zasilania	41	10.1	10.4	10.8	11.2	11.5	11.9	12.3	12.8	13.2	13.6	14.1	14.6	15.0	15.5	16.0	16.6
	43	10.0	10.3	10.7	11.1	11.4	11.8	12.2	12.6	13.0	13.5	13.9	14.4	14.9	15.3	15.8	16.4
	45	9.9	10.2	10.6	10.9	11.3	11.7	12.1	12.5	12.9	13.3	13.8	14.2	14.7	15.1	15.6	16.1
	47	9.8	10.2	10.5	10.8	11.2	11.6	11.9	12.3	12.7	13.2	13.6	14.0	14.5	15.0	15.4	15.9
	49	9.7	10.1	10.4	10.7	11.1	11.4	11.8	12.2	12.6	13.0	13.4	13.9	14.3	14.8	15.2	15.7
	51	9.7	10.0	10.3	10.6	11.0	11.3	11.7	12.1	12.4	12.8	13.3	13.7	14.1	14.6	15.0	15.5
	53	9.6	9.9	10.2	10.5	10.9	11.2	11.6	11.9	12.3	12.7	13.1	13.5	14.0	14.4	14.9	15.3
	55	9.5	9.8	10.1	10.4	10.8	11.1	11.4	11.8	12.2	12.6	12.9	13.4	13.8	14.2	14.7	15.1
	57	9.4	9.7	10.0	10.3	10.6	11.0	11.3	11.7	12.0	12.4	12.8	13.2	13.6	14.0	14.5	14.9
	59	9.4	9.6	9.9	10.2	10.5	10.9	11.2	11.5	11.9	12.3	12.6	13.0	13.4	13.9	14.3	14.7
	61	9.3	9.6	9.9	10.2	10.5	10.8	11.1	11.4	11.8	12.1	12.5	12.9	13.3	13.7	14.1	14.5
	63	9.2	9.5	9.8	10.1	10.4	10.7	11.0	11.3	11.6	12.0	12.3	12.7	13.1	13.5	13.9	14.3
	65	9.2	9.4	9.7	10.0	10.3	10.6	10.9	11.2	11.5	11.9	12.2	12.6	12.9	13.3	13.7	14.1
	67	9.1	9.4	9.6	9.9	10.2	10.5	10.8	11.1	11.4	11.7	12.1	12.4	12.8	13.2	13.5	14.0
	69	9.1	9.3	9.6	9.8	10.1	10.4	10.7	11.0	11.3	11.6	11.9	12.3	12.6	13.0	13.4	13.8
	71		9.3	9.5	9.8	10.0	10.3	10.6	10.9	11.2	11.5	11.8	12.1	12.5	12.8	13.2	13.6
73				9.7	10.0	10.2	10.5	10.8	11.1	11.4	11.7	12.0	12.3	12.7	13.0	13.4	
75						10.1	10.4	10.7	10.9	11.2	11.5	11.8	12.2	12.5	12.8	13.2	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.5	4.7	4.8	5.0	5.1	5.3	5.4	5.6	5.8	6.0	6.2	6.4	6.5	6.7	6.9	7.1
	43	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.8	6.0	6.2	6.4	6.5	6.8
	45	4.1	4.2	4.3	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.5	5.7	5.9	6.0	6.2	6.4
	47	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	4.9	5.1	5.3	5.4	5.6	5.7	5.9	6.1
	49	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.6	4.7	4.9	5.0	5.1	5.3	5.4	5.6	5.7
	51	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.4	4.6	4.7	4.9	5.0	5.1	5.3	5.4
	53	3.3	3.4	3.5	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.7	4.9	5.0	5.2
	55	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.8	4.9
	57	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.3	4.4	4.5	4.6
	59	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.2	4.3	4.4
	61	2.7	2.8	2.9	3.0	3.1	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1
	63	2.6	2.7	2.7	2.8	2.9	3.0	3.1	3.2	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9
	65	2.5	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.2	3.3	3.4	3.5	3.6	3.7
	67	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.2	3.3	3.4	3.5
	69	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.1	3.2	3.3
	71		2.2	2.2	2.3	2.4	2.4	2.5	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.1
73				2.2	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.8	2.8	2.9	3.0	
75						2.2	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.7	2.8	

Temperatura zasilania źródła dolnego

6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	9.6	10.0	10.5	10.9	11.4	11.8	12.3	12.8	13.3	13.8	14.4	14.9	15.5	16.0	16.6	17.2
	43	9.4	9.8	10.2	10.6	11.1	11.6	12.0	12.5	13.0	13.5	14.0	14.6	15.1	15.7	16.3	16.9
	45	9.1	9.5	9.9	10.4	10.8	11.3	11.7	12.2	12.7	13.2	13.7	14.2	14.8	15.3	15.9	16.5
	47	8.9	9.3	9.7	10.1	10.5	11.0	11.4	11.9	12.4	12.9	13.4	13.9	14.4	15.0	15.5	16.1
	49	8.6	9.0	9.4	9.8	10.2	10.7	11.1	11.6	12.1	12.5	13.0	13.5	14.1	14.6	15.1	15.7
	51	8.4	8.8	9.1	9.5	10.0	10.4	10.8	11.3	11.7	12.2	12.7	13.2	13.7	14.2	14.8	15.3
	53	8.1	8.5	8.9	9.3	9.7	10.1	10.5	10.9	11.4	11.9	12.3	12.8	13.3	13.9	14.4	14.9
	55	7.9	8.2	8.6	9.0	9.4	9.8	10.2	10.6	11.1	11.5	12.0	12.5	13.0	13.5	14.0	14.5
	57	7.6	7.9	8.3	8.7	9.1	9.5	9.9	10.3	10.7	11.2	11.6	12.1	12.6	13.1	13.6	14.1
	59	7.3	7.7	8.0	8.4	8.8	9.1	9.5	10.0	10.4	10.8	11.3	11.7	12.2	12.7	13.2	13.7
	61	7.1	7.4	7.7	8.1	8.5	8.8	9.2	9.6	10.0	10.5	10.9	11.4	11.8	12.3	12.8	13.3
	63	6.8	7.1	7.5	7.8	8.2	8.5	8.9	9.3	9.7	10.1	10.5	11.0	11.4	11.9	12.4	12.9
	65	6.5	6.9	7.2	7.5	7.8	8.2	8.6	8.9	9.3	9.7	10.2	10.6	11.0	11.5	12.0	12.4
	67	6.3	6.6	6.9	7.2	7.5	7.9	8.2	8.6	9.0	9.4	9.8	10.2	10.6	11.1	11.5	12.0
	69	6.0	6.3	6.6	6.9	7.2	7.6	7.9	8.3	8.6	9.0	9.4	9.8	10.2	10.7	11.1	11.6
	71		6.0	6.3	6.6	6.9	7.2	7.6	7.9	8.3	8.6	9.0	9.4	9.8	10.2	10.7	11.1
73				6.3	6.6	6.9	7.2	7.6	7.9	8.3	8.6	9.0	9.4	9.8	10.2	10.7	
75						6.6	6.9	7.2	7.5	7.9	8.2	8.6	9.0	9.4	9.8	10.2	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	2.6	2.6	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	
	43	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8	2.8
	45	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9	2.9
	47	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1
	49	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
	51	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3
	53	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	55	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6
	57	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8
	59	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
	61	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2
	63	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
	65	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
	67	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
	69	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
	71		5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
73				5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.5	5.5	5.5	5.5	5.5	5.5	
75						5.9	5.9	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	

Moc grzewcza (kW)

Temperatura zasilania	41	12.0	12.5	12.9	13.3	13.8	14.2	14.7	15.2	15.7	16.2	16.8	17.3	17.9	18.4	19.0	19.6
	43	11.9	12.3	12.7	13.2	13.6	14.1	14.5	15.0	15.5	16.0	16.5	17.1	17.6	18.2	18.8	19.4
	45	11.8	12.2	12.6	13.0	13.4	13.9	14.4	14.8	15.3	15.8	16.3	16.9	17.4	18.0	18.5	19.1
	47	11.7	12.0	12.4	12.9	13.3	13.7	14.2	14.7	15.1	15.6	16.1	16.6	17.2	17.7	18.3	18.8
	49	11.5	11.9	12.3	12.7	13.1	13.6	14.0	14.5	14.9	15.4	15.9	16.4	16.9	17.5	18.0	18.6
	51	11.4	11.8	12.2	12.6	13.0	13.4	13.8	14.3	14.7	15.2	15.7	16.2	16.7	17.2	17.8	18.3
	53	11.3	11.7	12.0	12.4	12.8	13.2	13.7	14.1	14.6	15.0	15.5	16.0	16.5	17.0	17.5	18.1
	55	11.2	11.6	11.9	12.3	12.7	13.1	13.5	13.9	14.4	14.8	15.3	15.7	16.2	16.7	17.3	17.8
	57	11.1	11.5	11.8	12.2	12.6	12.9	13.4	13.8	14.2	14.6	15.1	15.5	16.0	16.5	17.0	17.5
	59	11.0	11.4	11.7	12.1	12.4	12.8	13.2	13.6	14.0	14.5	14.9	15.3	15.8	16.3	16.8	17.3
	61	10.9	11.3	11.6	11.9	12.3	12.7	13.1	13.4	13.9	14.3	14.7	15.1	15.6	16.1	16.5	17.0
	63	10.9	11.2	11.5	11.8	12.2	12.5	12.9	13.3	13.7	14.1	14.5	15.0	15.4	15.8	16.3	16.8
	65	10.8	11.1	11.4	11.7	12.1	12.4	12.8	13.2	13.5	13.9	14.3	14.8	15.2	15.6	16.1	16.6
	67	10.8	11.1	11.4	11.7	12.0	12.3	12.7	13.0	13.4	13.8	14.2	14.6	15.0	15.4	15.9	16.3
	69	10.7	11.0	11.3	11.6	11.9	12.2	12.6	12.9	13.3	13.6	14.0	14.4	14.8	15.2	15.7	16.1
	71		11.0	11.2	11.5	11.8	12.1	12.5	12.8	13.1	13.5	13.9	14.2	14.6	15.0	15.4	15.9
73				11.5	11.8	12.1	12.4	12.7	13.0	13.4	13.7	14.1	14.5	14.9	15.2	15.7	
75						12.0	12.3	12.6	12.9	13.2	13.6	13.9	14.3	14.7	15.1	15.5	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.9	6.0	6.3	6.5	6.7	6.8	7.0	7.3
	43	4.3	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.6	5.7	5.9	6.1	6.3	6.5	6.7	6.9
	45	4.1	4.2	4.3	4.5	4.6	4.8	4.9	5.1	5.3	5.4	5.6	5.8	5.9	6.1	6.3	6.5
	47	3.9	4.0	4.1	4.2	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.4	5.6	5.8	6.0	6.1
	49	3.6	3.8	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.5	5.6	5.8
	51	3.4	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.3	5.5
	53	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.0	5.2
	55	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.5	4.6	4.8	4.9
	57	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.5	4.6
	59	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.4
	61	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.8	3.9	4.0	4.1
	63	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.8	3.9
	65	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6
	67	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4
	69	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2
	71		2.1	2.1	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0
73				2.1	2.1	2.2	2.2	2.3	2.3	2.4	2.5	2.6	2.6	2.7	2.8	2.9	
75						2.0	2.1	2.2	2.2	2.3	2.3	2.4	2.5	2.6	2.6	2.7	

Temperatura zasilania źródła dolnego

6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	10.8	11.2	11.7	12.2	12.6	13.1	13.7	14.2	14.8	15.3	15.9	16.5	17.1	17.7	18.4	19.1
	43	10.5	11.0	11.4	11.9	12.4	12.9	13.4	13.9	14.4	15.0	15.5	16.1	16.7	17.4	18.0	18.7
	45	10.3	10.7	11.1	11.6	12.1	12.6	13.1	13.6	14.1	14.7	15.2	15.8	16.4	17.0	17.6	18.2
	47	10.0	10.4	10.9	11.3	11.8	12.3	12.7	13.3	13.8	14.3	14.9	15.4	16.0	16.6	17.2	17.8
	49	9.8	10.2	10.6	11.0	11.5	12.0	12.4	12.9	13.4	14.0	14.5	15.0	15.6	16.2	16.8	17.4
	51	9.5	9.9	10.3	10.7	11.2	11.6	12.1	12.6	13.1	13.6	14.1	14.7	15.2	15.8	16.4	17.0
	53	9.2	9.6	10.0	10.5	10.9	11.3	11.8	12.3	12.8	13.3	13.8	14.3	14.9	15.4	16.0	16.6
	55	9.0	9.4	9.8	10.2	10.6	11.0	11.5	11.9	12.4	12.9	13.4	13.9	14.5	15.0	15.6	16.1
	57	8.7	9.1	9.5	9.9	10.3	10.7	11.2	11.6	12.1	12.6	13.0	13.6	14.1	14.6	15.1	15.7
	59	8.4	8.8	9.2	9.6	10.0	10.4	10.8	11.3	11.7	12.2	12.7	13.2	13.7	14.2	14.7	15.3
	61	8.2	8.5	8.9	9.3	9.7	10.1	10.5	10.9	11.4	11.8	12.3	12.8	13.3	13.8	14.3	14.9
	63	7.9	8.2	8.6	9.0	9.4	9.8	10.2	10.6	11.0	11.5	11.9	12.4	12.9	13.4	13.9	14.4
	65	7.6	8.0	8.3	8.7	9.0	9.4	9.8	10.2	10.7	11.1	11.5	12.0	12.5	13.0	13.5	14.0
	67	7.3	7.7	8.0	8.4	8.7	9.1	9.5	9.9	10.3	10.7	11.1	11.6	12.1	12.5	13.0	13.5
	69	7.0	7.4	7.7	8.0	8.4	8.8	9.1	9.5	9.9	10.3	10.8	11.2	11.6	12.1	12.6	13.1
	71		7.1	7.4	7.7	8.1	8.4	8.8	9.2	9.5	9.9	10.4	10.8	11.2	11.7	12.1	12.6
73				7.4	7.7	8.1	8.4	8.8	9.2	9.6	10.0	10.4	10.8	11.2	11.7	12.1	
75						7.7	8.1	8.4	8.8	9.2	9.6	10.0	10.4	10.8	11.2	11.7	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.1	3.1	3.1	3.1	
	43	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.1	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
	45	3.2	3.2	3.2	3.2	3.2	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.3	3.4	3.4	3.4
	47	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.4	3.5	3.5	3.5	3.5	3.5	3.5
	49	3.5	3.5	3.5	3.5	3.5	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.7
	51	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.7	3.8	3.8	3.8	3.8	3.8	3.8	3.8
	53	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	3.9	4.0	4.0	4.0	4.0
	55	4.0	4.0	4.0	4.0	4.0	4.0	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.2
	57	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
	59	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.5	4.5	4.5	4.5	4.5	4.5	4.5
	61	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.7	4.7	4.7	4.7	4.7	4.7	4.7
	63	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.9	4.9	4.9	4.9	4.9	4.9	4.9
	65	5.0	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
	67	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.4	5.4	5.4
	69	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.6	5.6	5.6	5.6	5.6	5.6	5.6
	71		5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
73				6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.1	6.1	6.1	6.1	6.1	6.1	6.1	
75						6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.4	6.4	

Moc grzewcza (kW)

Temperatura zasilania	41	13.5	13.9	14.4	14.8	15.3	15.8	16.3	16.9	17.4	18.0	18.6	19.2	19.8	20.5	21.1	21.8	
	43	13.3	13.8	14.2	14.7	15.2	15.7	16.2	16.7	17.2	17.8	18.4	19.0	19.6	20.2	20.9	21.5	21.5
	45	13.2	13.6	14.1	14.6	15.0	15.5	16.0	16.5	17.0	17.6	18.2	18.7	19.3	20.0	20.6	21.3	21.3
	47	13.1	13.5	14.0	14.4	14.9	15.3	15.8	16.3	16.8	17.4	17.9	18.5	19.1	19.7	20.3	21.0	21.0
	49	13.0	13.4	13.8	14.3	14.7	15.2	15.6	16.1	16.7	17.2	17.7	18.3	18.9	19.5	20.1	20.7	20.7
	51	12.9	13.3	13.7	14.1	14.6	15.0	15.5	16.0	16.5	17.0	17.5	18.1	18.6	19.2	19.8	20.4	20.4
	53	12.8	13.2	13.6	14.0	14.4	14.9	15.3	15.8	16.3	16.8	17.3	17.8	18.4	19.0	19.6	20.2	20.2
	55	12.7	13.1	13.5	13.9	14.3	14.7	15.2	15.6	16.1	16.6	17.1	17.6	18.2	18.7	19.3	19.9	19.9
	57	12.6	13.0	13.3	13.7	14.2	14.6	15.0	15.5	15.9	16.4	16.9	17.4	17.9	18.5	19.1	19.6	19.6
	59	12.5	12.9	13.2	13.6	14.0	14.5	14.9	15.3	15.8	16.2	16.7	17.2	17.7	18.3	18.8	19.4	19.4
	61	12.4	12.8	13.1	13.5	13.9	14.3	14.7	15.1	15.6	16.0	16.5	17.0	17.5	18.0	18.6	19.1	19.1
	63	12.3	12.7	13.0	13.4	13.8	14.2	14.6	15.0	15.4	15.9	16.3	16.8	17.3	17.8	18.3	18.9	18.9
	65	12.3	12.6	13.0	13.3	13.7	14.1	14.5	14.9	15.3	15.7	16.2	16.6	17.1	17.6	18.1	18.6	18.6
	67	12.2	12.5	12.9	13.2	13.6	14.0	14.3	14.7	15.1	15.5	16.0	16.4	16.9	17.4	17.9	18.4	18.4
	69	12.1	12.5	12.8	13.1	13.5	13.8	14.2	14.6	15.0	15.4	15.8	16.2	16.7	17.2	17.6	18.1	18.1
	71		12.4	12.7	13.0	13.4	13.7	14.1	14.5	14.9	15.2	15.6	16.1	16.5	17.0	17.4	17.9	17.9
73				13.0	13.3	13.6	14.0	14.4	14.7	15.1	15.5	15.9	16.3	16.8	17.2	17.7	17.7	
75						13.6	13.9	14.2	14.6	15.0	15.3	15.7	16.1	16.6	17.0	17.5	17.5	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.8	6.0	6.2	6.3	6.5	6.7	6.9	7.1	
	43	4.3	4.5	4.6	4.7	4.9	5.1	5.2	5.3	5.5	5.7	5.8	6.0	6.2	6.3	6.5	6.7	6.7
	45	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.5	5.7	5.8	6.0	6.2	6.3	6.3
	47	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	4.9	5.1	5.2	5.4	5.5	5.7	5.8	6.0	6.0
	49	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.5	4.7	4.8	4.9	5.1	5.2	5.4	5.5	5.7	5.7
	51	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4	4.6	4.7	4.8	4.9	5.1	5.2	5.4	5.4
	53	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4	4.5	4.7	4.8	5.0	5.1	5.1
	55	3.2	3.3	3.3	3.4	3.5	3.6	3.8	3.8	4.0	4.1	4.2	4.3	4.4	4.5	4.7	4.8	4.8
	57	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.5	4.5
	59	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.3
	61	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.1
	63	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.7	3.9	3.9
	65	2.5	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.7
	67	2.3	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.4	3.4
	69	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.2	3.2
	71		2.2	2.2	2.3	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.1
73				2.2	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.6	2.7	2.8	2.8	2.9	2.9	
75						2.2	2.2	2.3	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.8	

Temperatura zasilania źródła dolnego

6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21

Moc chłodnicza kW

Temperatura zasilania	41	11.7	12.2	12.7	13.2	13.7	14.3	14.8	15.4	16.0	16.6	17.3	17.9	18.6	19.3	20.0	20.7
	43	11.4	11.9	12.4	12.9	13.4	14.0	14.5	15.1	15.7	16.3	16.9	17.5	18.2	18.9	19.6	20.3
	45	11.2	11.6	12.1	12.6	13.1	13.7	14.2	14.8	15.3	15.9	16.5	17.2	17.8	18.5	19.2	19.9
	47	10.9	11.4	11.8	12.3	12.8	13.3	13.9	14.4	15.0	15.5	16.1	16.8	17.4	18.1	18.7	19.4
	49	10.6	11.1	11.5	12.0	12.5	13.0	13.5	14.1	14.6	15.2	15.8	16.4	17.0	17.7	18.3	19.0
	51	10.4	10.8	11.2	11.7	12.2	12.7	13.2	13.7	14.3	14.8	15.4	16.0	16.6	17.2	17.9	18.6
	53	10.1	10.5	11.0	11.4	11.9	12.4	12.9	13.4	13.9	14.5	15.0	15.6	16.2	16.8	17.4	18.1
	55	9.8	10.2	10.7	11.1	11.6	12.0	12.5	13.0	13.5	14.1	14.6	15.2	15.8	16.4	17.0	17.6
	57	9.5	9.9	10.4	10.8	11.2	11.7	12.2	12.7	13.2	13.7	14.2	14.8	15.4	15.9	16.6	17.2
	59	9.2	9.6	10.0	10.5	10.9	11.4	11.8	12.3	12.8	13.3	13.8	14.4	15.0	15.5	16.1	16.7
	61	9.0	9.3	9.7	10.2	10.6	11.0	11.5	11.9	12.4	12.9	13.4	14.0	14.5	15.1	15.7	16.3
	63	8.7	9.0	9.4	9.8	10.3	10.7	11.1	11.6	12.0	12.5	13.0	13.6	14.1	14.6	15.2	15.8
	65	8.4	8.7	9.1	9.5	9.9	10.3	10.8	11.2	11.7	12.1	12.6	13.1	13.7	14.2	14.7	15.3
	67	8.1	8.4	8.8	9.2	9.6	10.0	10.4	10.8	11.3	11.7	12.2	12.7	13.2	13.7	14.3	14.8
	69	7.8	8.1	8.5	8.9	9.2	9.6	10.0	10.4	10.9	11.3	11.8	12.3	12.8	13.3	13.8	14.3
	71		7.8	8.1	8.6	8.9	9.3	9.7	10.0	10.5	10.9	11.3	11.8	12.3	12.8	13.3	13.8
73				8.3	8.5	8.9	9.3	9.6	10.1	10.5	10.9	11.4	11.9	12.4	12.8	13.3	
75							9.0	9.2	9.7	10.1	10.4	10.9	11.4	11.9	12.3	12.8	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5	3.5
	43	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6	3.6
	45	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8	3.8
	47	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0	4.0
	49	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1	4.1
	51	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3
	53	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
	55	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7	4.7
	57	4.8	4.8	4.8	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9
	59	5.0	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
	61	5.2	5.2	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
	63	5.4	5.4	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.6	5.6	5.6	5.6
	65	5.6	5.6	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.8	5.8	5.8	5.8	5.8	5.8	5.8
	67	5.8	5.9	5.9	5.9	5.9	5.9	5.9	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
	69	6.0	6.1	6.1	6.1	6.1	6.1	6.2	6.2	6.2	6.2	6.2	6.2	6.3	6.3	6.3	6.3
	71		6.4	6.3	6.4	6.3	6.3	6.4	6.4	6.4	6.5	6.5	6.4	6.5	6.5	6.5	6.5
73				6.6	6.5	6.5	6.7	6.6	6.6	6.7	6.7	6.6	6.8	6.8	6.8	6.8	
75							6.9	6.8	6.8	7.0	7.0	6.8	7.0	7.0	7.0	7.0	

Moc grzewcza (kW)

Temperatura zasilania	41	14.9	15.3	15.8	16.3	16.9	17.4	18.0	18.6	19.2	19.8	20.4	21.0	21.7	22.4	23.1	23.8
	43	14.8	15.2	15.7	16.2	16.7	17.2	17.8	18.4	18.9	19.6	20.2	20.8	21.5	22.1	22.8	23.6
	45	14.6	15.1	15.6	16.1	16.6	17.1	17.6	18.2	18.8	19.3	19.9	20.6	21.2	21.9	22.6	23.3
	47	14.5	15.0	15.4	15.9	16.4	16.9	17.4	18.0	18.6	19.1	19.7	20.3	21.0	21.6	22.3	23.0
	49	14.4	14.9	15.3	15.8	16.3	16.8	17.3	17.8	18.4	18.9	19.5	20.1	20.7	21.4	22.0	22.7
	51	14.3	14.7	15.2	15.6	16.1	16.6	17.1	17.6	18.2	18.7	19.3	19.9	20.5	21.1	21.8	22.4
	53	14.2	14.6	15.0	15.5	16.0	16.4	16.9	17.5	18.0	18.5	19.1	19.7	20.3	20.9	21.5	22.2
	55	14.1	14.5	14.9	15.4	15.8	16.3	16.8	17.3	17.8	18.3	18.9	19.4	20.0	20.6	21.3	21.9
	57	14.0	14.4	14.8	15.2	15.7	16.1	16.6	17.1	17.6	18.1	18.7	19.2	19.8	20.4	21.0	21.6
	59	13.9	14.3	14.7	15.1	15.5	16.0	16.5	16.9	17.4	17.9	18.5	19.0	19.6	20.2	20.7	21.4
	61	13.8	14.2	14.6	15.0	15.4	15.8	16.3	16.8	17.3	17.8	18.3	18.8	19.3	19.9	20.5	21.1
	63	13.7	14.1	14.5	14.9	15.3	15.7	16.1	16.6	17.1	17.6	18.1	18.6	19.1	19.7	20.2	20.8
	65	13.6	14.0	14.3	14.7	15.1	15.5	16.0	16.4	16.9	17.4	17.9	18.4	18.9	19.4	20.0	20.6
	67	13.5	13.8	14.2	14.6	15.0	15.4	15.8	16.3	16.7	17.2	17.7	18.2	18.7	19.2	19.7	20.3
	69	13.4	13.7	14.1	14.5	14.9	15.3	15.7	16.1	16.5	17.0	17.5	18.0	18.5	19.0	19.5	20.0
	71		13.5	14.0	14.3	14.7	15.2	15.6	15.9	16.3	16.8	17.3	17.8	18.3	18.8	19.3	19.7
73				14.2	14.6	15.1	15.5	15.7	16.1	16.6	17.1	17.6	18.1	18.6	19.1	19.4	
75							15.4	15.5	15.9	16.4	16.9	17.4	17.9	18.4	18.9	19.1	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.3	4.4	4.5	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.9	6.0	6.2	6.4	6.6	6.8
	43	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.1	5.2	5.4	5.6	5.7	5.9	6.1	6.3	6.5
	45	3.9	4.0	4.1	4.3	4.4	4.5	4.6	4.8	5.0	5.1	5.3	5.4	5.6	5.8	6.0	6.2
	47	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.6	4.7	4.8	5.0	5.1	5.3	5.5	5.7	5.8
	49	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.0	5.2	5.3	5.5
	51	3.3	3.4	3.5	3.6	3.7	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.1	5.2
	53	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	4.9
	55	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.5	4.7
	57	2.9	3.0	3.1	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4
	59	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.5	3.6	3.7	3.8	4.0	4.1	4.2
	61	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.6	3.8	3.9	4.0
	63	2.5	2.6	2.7	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.4	3.6	3.6	3.8
	65	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6
	67	2.3	2.4	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4
	69	2.2	2.2	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.7	2.8	2.9	3.0	3.0	3.1	3.2
	71		2.1	2.2	2.3	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.0
73				2.1	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.8	2.9	
75							2.2	2.3	2.4	2.4	2.4	2.6	2.6	2.6	2.7	2.7	

Temperatura zasilania źródła dolnego

	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
--	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	14.4	15.0	15.6	16.2	16.9	17.6	18.3	19.0	19.8	20.6	21.4	22.2	23.0	23.9	24.8	25.7
	43	14.0	14.6	15.2	15.9	16.5	17.2	17.9	18.6	19.4	20.1	20.9	21.7	22.5	23.4	24.2	25.1
	45	13.7	14.3	14.9	15.5	16.1	16.8	17.5	18.2	18.9	19.7	20.4	21.2	22.0	22.9	23.7	24.6
	47	13.4	13.9	14.5	15.1	15.7	16.4	17.1	17.8	18.5	19.2	20.0	20.7	21.5	22.4	23.2	24.1
	49	13.0	13.6	14.2	14.8	15.4	16.0	16.7	17.3	18.0	18.7	19.5	20.2	21.0	21.8	22.7	23.5
	51	12.7	13.2	13.8	14.4	15.0	15.6	16.2	16.9	17.6	18.3	19.0	19.7	20.5	21.3	22.1	22.9
	53	12.3	12.9	13.4	14.0	14.6	15.2	15.8	16.4	17.1	17.8	18.5	19.2	20.0	20.8	21.5	22.4
	55	12.0	12.5	13.0	13.6	14.2	14.8	15.4	16.0	16.6	17.3	18.0	18.7	19.5	20.2	21.0	21.8
	57	11.6	12.1	12.7	13.2	13.8	14.3	14.9	15.5	16.2	16.8	17.5	18.2	18.9	19.7	20.4	21.2
	59	11.3	11.8	12.3	12.8	13.4	13.9	14.5	15.1	15.7	16.3	17.0	17.7	18.4	19.1	19.8	20.6
	61	10.9	11.4	11.9	12.4	12.9	13.5	14.1	14.6	15.2	15.8	16.5	17.1	17.8	18.5	19.3	20.0
	63	10.6	11.1	11.5	12.0	12.5	13.1	13.6	14.2	14.8	15.3	16.0	16.6	17.3	18.0	18.7	19.4
	65	10.3	10.7	11.2	11.6	12.1	12.6	13.2	13.7	14.3	14.9	15.5	16.1	16.7	17.4	18.1	18.8
	67	9.9	10.4	10.8	11.2	11.7	12.2	12.7	13.3	13.8	14.4	15.0	15.5	16.2	16.8	17.5	18.2
	69	9.6	10.0	10.4	10.9	11.3	11.8	12.3	12.8	13.3	13.9	14.4	15.0	15.6	16.2	16.9	17.5
	71		9.7	10.1	10.5	10.9	11.3	11.8	12.3	12.8	13.4	13.9	14.5	15.0	15.6	16.3	16.8
73				10.2	10.5	10.9	11.4	11.8	12.3	12.9	13.3	14.0	14.4	15.0	15.7	16.1	
75							10.9	11.3	11.8	12.4	12.8	13.5	13.8	14.4	15.1	15.4	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	4.2	4.2	4.2	4.2	4.2	4.2	4.2	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	4.3	
	43	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.5	4.5	4.5	4.5
	45	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6	4.6
	47	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8
	49	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
	51	5.2	5.2	5.2	5.2	5.2	5.2	5.2	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3
	53	5.4	5.4	5.4	5.4	5.4	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.5
	55	5.6	5.6	5.6	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.7	5.8	5.8	5.8
	57	5.8	5.8	5.9	5.9	5.9	5.9	5.9	5.9	5.9	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0
	59	6.1	6.1	6.1	6.1	6.1	6.1	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.2	6.3	6.3
	61	6.3	6.3	6.3	6.4	6.4	6.4	6.4	6.4	6.4	6.4	6.5	6.5	6.5	6.5	6.5	6.5	6.5
	63	6.5	6.6	6.6	6.6	6.6	6.6	6.7	6.7	6.7	6.7	6.7	6.7	6.7	6.8	6.8	6.8	6.8
	65	6.8	6.8	6.8	6.8	6.9	6.9	6.9	6.9	7.0	7.0	7.0	7.0	7.0	7.0	7.1	7.1	7.1
	67	7.0	7.0	7.1	7.1	7.1	7.2	7.2	7.2	7.2	7.2	7.3	7.3	7.3	7.3	7.3	7.3	7.4
	69	7.3	7.3	7.3	7.4	7.4	7.4	7.4	7.4	7.5	7.5	7.5	7.5	7.6	7.6	7.6	7.6	7.7
	71		7.5	7.6	7.7	7.6	7.7	7.7	7.7	7.7	7.7	7.8	7.8	7.9	7.8	7.9	7.9	8.0
73				8.0	7.9	7.9	7.9	8.0	8.0	8.1	8.0	8.2	8.1	8.2	8.2	8.2	8.3	
75							8.2	8.2	8.2	8.4	8.3	8.5	8.3	8.5	8.5	8.5	8.6	

Moc grzewcza (kW)

Temperatura zasilania	41	18.2	18.8	19.4	20.1	20.7	21.4	22.2	22.9	23.6	24.4	25.2	26.0	26.8	27.7	28.6	29.5
	43	18.0	18.6	19.2	19.9	20.5	21.2	21.9	22.6	23.4	24.1	24.9	25.7	26.5	27.4	28.2	29.1
	45	17.9	18.4	19.1	19.7	20.3	21.0	21.7	22.4	23.1	23.9	24.6	25.4	26.2	27.0	27.9	28.8
	47	17.7	18.3	18.9	19.5	20.1	20.8	21.5	22.1	22.9	23.6	24.3	25.1	25.9	26.7	27.6	28.4
	49	17.5	18.1	18.7	19.3	19.9	20.6	21.2	21.9	22.6	23.3	24.1	24.8	25.6	26.4	27.2	28.0
	51	17.4	18.0	18.5	19.1	19.7	20.4	21.0	21.7	22.3	23.1	23.8	24.5	25.3	26.1	26.9	27.7
	53	17.3	17.8	18.4	18.9	19.5	20.1	20.8	21.4	22.1	22.8	23.5	24.2	25.0	25.7	26.5	27.3
	55	17.1	17.6	18.2	18.8	19.3	19.9	20.6	21.2	21.8	22.5	23.2	23.9	24.7	25.4	26.2	27.0
	57	17.0	17.5	18.0	18.6	19.1	19.7	20.3	21.0	21.6	22.3	22.9	23.6	24.3	25.1	25.8	26.6
	59	16.8	17.3	17.9	18.4	19.0	19.5	20.1	20.7	21.3	22.0	22.7	23.3	24.0	24.8	25.5	26.3
	61	16.7	17.2	17.7	18.2	18.8	19.3	19.9	20.5	21.1	21.7	22.4	23.0	23.7	24.4	25.2	25.9
	63	16.6	17.1	17.6	18.1	18.6	19.1	19.7	20.3	20.9	21.5	22.1	22.8	23.4	24.1	24.8	25.6
	65	16.5	16.9	17.4	17.9	18.4	19.0	19.5	20.1	20.6	21.2	21.8	22.5	23.1	23.8	24.5	25.2
	67	16.4	16.8	17.3	17.8	18.3	18.8	19.3	19.8	20.4	21.0	21.6	22.2	22.8	23.5	24.2	24.9
	69	16.3	16.7	17.2	17.6	18.1	18.6	19.1	19.6	20.2	20.8	21.3	21.9	22.6	23.2	23.8	24.5
	71		16.6	17.1	17.4	17.9	18.4	18.9	19.4	20.0	20.6	21.0	21.6	22.4	22.9	23.4	24.1
73				17.2	17.7	18.2	18.7	19.2	19.8	20.4	20.7	21.3	22.2	22.6	23.0	23.7	
75							18.5	19.0	19.6	20.2	20.4	21.0	22.0	22.3	22.6	23.3	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.3	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.6	5.7	5.9	6.1	6.3	6.5	6.7	6.9
	43	4.1	4.2	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.4	5.6	5.8	6.0	6.2	6.3	6.5
	45	3.9	4.0	4.2	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.8	6.0	6.2
	47	3.7	3.8	4.0	4.1	4.2	4.3	4.5	4.6	4.8	4.9	5.0	5.2	5.4	5.5	5.7	5.9
	49	3.5	3.6	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.5
	51	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	5.0	5.1	5.3
	53	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4	4.6	4.7	4.8	5.0
	55	3.1	3.1	3.3	3.3	3.4	3.5	3.7	3.7	3.8	4.0	4.1	4.2	4.3	4.4	4.6	4.7
	57	2.9	3.0	3.1	3.2	3.3	3.3	3.4	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4
	59	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2
	61	2.7	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0
	63	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8
	65	2.4	2.5	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.1	3.2	3.3	3.4	3.5	3.6
	67	2.3	2.4	2.5	2.5	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.1	3.2	3.3	3.4
	69	2.3	2.3	2.4	2.4	2.5	2.5	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.1	3.2
	71		2.2	2.3	2.3	2.4	2.4	2.5	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.0
73				2.2	2.3	2.3	2.4	2.4	2.5	2.5	2.6	2.6	2.8	2.8	2.8	2.9	
75							2.3	2.3	2.4	2.4	2.5	2.5	2.7	2.6	2.7	2.7	

Temperatura zasilania źródła dolnego

	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21
--	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----

Moc chłodnicza kW

Temperatura zasilania	41	16.6	17.3	18.0	18.8	19.6	20.4	21.2	22.1	22.9	23.8	24.8	25.7	26.7	27.7	28.7	29.7
	43	16.2	16.9	17.6	18.4	19.1	19.9	20.7	21.6	22.4	23.3	24.2	25.2	26.1	27.1	28.1	29.1
	45	15.8	16.5	17.2	18.0	18.7	19.5	20.3	21.1	21.9	22.8	23.7	24.6	25.5	26.5	27.5	28.5
	47	15.4	16.1	16.8	17.5	18.3	19.0	19.8	20.6	21.4	22.3	23.1	24.0	25.0	25.9	26.9	27.9
	49	15.1	15.7	16.4	17.1	17.8	18.5	19.3	20.1	20.9	21.7	22.6	23.5	24.4	25.3	26.3	27.2
	51	14.7	15.3	15.9	16.6	17.3	18.1	18.8	19.6	20.4	21.2	22.0	22.9	23.8	24.7	25.6	26.6
	53	14.3	14.9	15.5	16.2	16.9	17.6	18.3	19.1	19.8	20.6	21.4	22.3	23.2	24.1	25.0	25.9
	55	13.9	14.5	15.1	15.7	16.4	17.1	17.8	18.5	19.3	20.1	20.9	21.7	22.5	23.4	24.3	25.2
	57	13.5	14.1	14.7	15.3	15.9	16.6	17.3	18.0	18.7	19.5	20.3	21.1	21.9	22.8	23.7	24.6
	59	13.1	13.6	14.2	14.8	15.5	16.1	16.8	17.5	18.2	18.9	19.7	20.5	21.3	22.1	23.0	23.9
	61	12.7	13.2	13.8	14.4	15.0	15.6	16.3	16.9	17.6	18.4	19.1	19.9	20.7	21.5	22.3	23.2
	63	12.3	12.8	13.4	13.9	14.5	15.1	15.8	16.4	17.1	17.8	18.5	19.3	20.0	20.8	21.6	22.5
	65	11.9	12.4	12.9	13.5	14.1	14.6	15.2	15.9	16.5	17.2	17.9	18.6	19.4	20.2	20.9	21.8
	67	11.5	12.0	12.5	13.0	13.6	14.2	14.7	15.3	16.0	16.6	17.3	18.0	18.7	19.5	20.3	21.0
	69	11.2	11.5	12.1	12.6	13.1	13.7	14.2	14.8	15.4	16.0	16.7	17.4	18.1	18.8	19.6	20.3
	71		11.1	11.6	12.1	12.7	13.2	13.7	14.3	14.8	15.4	16.1	16.8	17.5	18.1	18.9	19.6
	73				11.7	12.2	12.7	13.2	13.8	14.2	14.8	15.5	16.2	16.9	17.4	18.2	18.9
75							12.7	13.3	13.6	14.2	14.9	15.6	16.3	16.7	17.5	18.2	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	4.8	4.8	4.8	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9	4.9
	43	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1	5.1
	45	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.3	5.4	5.4	5.4	5.4
	47	5.5	5.5	5.5	5.5	5.5	5.5	5.5	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6	5.6
	49	5.7	5.7	5.7	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8	5.8
	51	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.0	6.1	6.1	6.1	6.1	6.1	6.1	6.1
	53	6.2	6.2	6.2	6.2	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3	6.3
	55	6.4	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.6	6.6	6.6	6.6	6.6	6.6	6.6	6.6
	57	6.7	6.7	6.7	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.9	6.9	6.9	6.9	6.9	6.9
	59	7.0	7.0	7.0	7.0	7.0	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.2	7.2	7.2	7.2
	61	7.2	7.2	7.3	7.3	7.3	7.3	7.4	7.4	7.4	7.4	7.4	7.4	7.5	7.5	7.5	7.5
	63	7.5	7.5	7.5	7.6	7.6	7.6	7.6	7.7	7.7	7.7	7.7	7.7	7.8	7.8	7.8	7.8
	65	7.8	7.8	7.8	7.9	7.9	7.9	7.9	8.0	8.0	8.0	8.0	8.0	8.1	8.1	8.1	8.1
	67	8.0	8.1	8.1	8.2	8.2	8.2	8.2	8.3	8.3	8.3	8.3	8.4	8.4	8.4	8.4	8.4
	69	8.3	8.4	8.4	8.4	8.5	8.5	8.5	8.6	8.6	8.6	8.6	8.7	8.7	8.7	8.8	8.8
	71		8.7	8.7	8.7	8.8	8.8	8.8	8.9	9.0	9.0	9.0	9.0	9.1	9.0	9.1	9.1
	73				8.9	9.1	9.1	9.1	9.2	9.3	9.2	9.4	9.3	9.4	9.3	9.5	9.5
75							9.4	9.5	9.7	9.5	9.7	9.6	9.8	9.6	9.8	9.8	

Moc grzewcza (kW)

Temperatura zasilania	41	21.0	21.7	22.5	23.2	24.0	24.8	25.6	26.5	27.3	28.2	29.2	30.0	31.0	32.0	33.0	34.0
	43	20.8	21.5	22.3	23.0	23.8	24.5	25.4	26.2	27.0	27.9	28.8	29.8	30.5	31.5	32.5	33.5
	45	20.6	21.3	22.0	22.8	23.5	24.3	25.1	25.9	26.7	27.6	28.5	29.4	30.5	31.5	32.5	33.5
	47	20.5	21.1	21.8	22.5	23.3	24.0	24.8	25.6	26.4	27.3	28.2	29.1	30.0	31.0	32.0	33.0
	49	20.3	20.9	21.6	22.3	23.0	23.8	24.6	25.3	26.1	27.0	27.8	28.7	29.6	30.5	31.5	32.5
	51	20.1	20.8	21.4	22.1	22.8	23.5	24.3	25.1	25.8	26.7	27.5	28.4	29.2	30.0	31.0	32.0
	53	19.9	20.6	21.2	21.9	22.6	23.3	24.0	24.8	25.6	26.3	27.2	28.0	28.9	29.8	30.5	31.5
	55	19.8	20.4	21.0	21.7	22.3	23.0	23.8	24.5	25.3	26.0	26.8	27.7	28.5	29.4	30.5	31.0
	57	19.6	20.2	20.8	21.5	22.1	22.8	23.5	24.2	25.0	25.7	26.5	27.3	28.2	29.0	29.9	31.0
	59	19.5	20.0	20.6	21.3	21.9	22.6	23.3	24.0	24.7	25.4	26.2	27.0	27.8	28.6	29.5	30.5
	61	19.3	19.9	20.5	21.1	21.7	22.3	23.0	23.7	24.4	25.1	25.9	26.6	27.4	28.3	29.1	30.0
	63	19.2	19.7	20.3	20.9	21.5	22.1	22.8	23.4	24.1	24.8	25.6	26.3	27.1	27.9	28.7	29.5
	65	19.0	19.6	20.1	20.7	21.3	21.9	22.5	23.2	23.8	24.5	25.3	26.0	26.7	27.5	28.3	29.1
	67	18.9	19.4	20.0	20.5	21.1	21.7	22.3	22.9	23.6	24.3	24.9	25.7	26.4	27.2	27.9	28.7
	69	18.8	19.2	19.8	20.4	20.9	21.5	22.1	22.7	23.3	24.0	24.6	25.3	26.1	26.8	27.6	28.3
	71		19.0	19.6	20.3	20.7	21.3	21.9	22.5	23.0	23.7	24.3	24.9	25.8	26.4	27.3	27.9
	73				20.2	20.5	21.1	21.7	22.3	22.7	23.4	24.0	24.5	25.5	26.0	27.0	27.5
75							21.5	22.1	22.4	23.1	23.7	24.1	25.2	25.6	26.7	27.1	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.4	4.5	4.7	4.8	4.9	5.1	5.3	5.4	5.6	5.8	6.0	6.1	6.3	6.5	6.7	6.9
	43	4.1	4.3	4.4	4.6	4.7	4.9	5.0	5.1	5.3	5.5	5.7	5.8	6.0	6.2	6.4	6.6
	45	3.9	4.1	4.2	4.3	4.4	4.6	4.7	4.9	5.0	5.2	5.4	5.6	5.7	5.9	6.1	6.3
	47	3.8	3.8	4.0	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.6	5.8	6.0
	49	3.6	3.7	3.8	3.9	4.0	4.1	4.3	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.4	5.6
	51	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4	4.6	4.7	4.8	5.0	5.1	5.3
	53	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.4	4.6	4.7	4.8	5.0
	55	3.1	3.2	3.3	3.4	3.4	3.5	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.7
	57	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5
	59	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.3
	61	2.7	2.8	2.8	2.9	3.0	3.1	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0
	63	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.2	3.3	3.4	3.5	3.6	3.7	3.8
	65	2.5	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.3	3.4	3.5	3.6
	67	2.4	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.2	3.3	3.4
	69	2.3	2.3	2.4	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.2
	71		2.2	2.3	2.4	2.4	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.9	2.9	3.0	3.1
	73				2.3	2.3	2.3	2.4	2.4	2.4	2.5	2.6	2.7	2.7	2.8	2.9	2.9
75							2.3	2.3	2.3	2.4	2.4	2.5	2.6	2.7	2.7	2.8	

Temperatura zasilania źródła dolnego

6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21

Moc chłodnicza kW

Temperatura zasilania	41	20.4	21.3	22.2	23.1	24.0	25.0	26.0	27.1	28.2	29.3	30.5	31.5	33.0	34.0	35.0	36.5
	43	19.9	20.8	21.7	22.6	23.5	24.5	25.5	26.5	27.6	28.6	29.7	31.0	32.0	33.5	34.5	36.0
	45	19.4	20.3	21.1	22.0	23.0	23.9	24.9	25.9	26.9	28.0	29.1	30.0	31.5	32.5	34.0	35.0
	47	19.0	19.8	20.6	21.5	22.4	23.3	24.3	25.3	26.3	27.3	28.4	29.5	30.5	32.0	33.0	34.0
	49	18.5	19.3	20.1	21.0	21.8	22.8	23.7	24.7	25.7	26.7	27.7	28.8	29.9	31.0	32.0	33.5
	51	18.0	18.8	19.6	20.4	21.3	22.2	23.1	24.0	25.0	26.0	27.0	28.1	29.2	30.5	31.5	32.5
	53	17.5	18.3	19.1	19.9	20.7	21.6	22.5	23.4	24.3	25.3	26.3	27.4	28.4	29.5	30.5	32.0
	55	17.0	17.8	18.5	19.3	20.1	21.0	21.8	22.8	23.7	24.6	25.6	26.6	27.7	28.8	29.9	31.0
	57	16.5	17.2	18.0	18.8	19.6	20.4	21.2	22.1	23.0	23.9	24.9	25.9	26.9	28.0	29.0	30.0
	59	16.0	16.7	17.4	18.2	19.0	19.8	20.6	21.5	22.3	23.2	24.2	25.2	26.1	27.2	28.2	29.3
	61	15.5	16.2	16.9	17.6	18.4	19.2	20.0	20.8	21.7	22.5	23.5	24.4	25.4	26.4	27.4	28.4
	63	15.1	15.7	16.4	17.1	17.8	18.6	19.3	20.1	21.0	21.8	22.7	23.6	24.6	25.6	26.6	27.6
	65	14.6	15.2	15.8	16.5	17.2	18.0	18.7	19.5	20.3	21.1	22.0	22.9	23.8	24.7	25.7	26.7
	67	14.1	14.7	15.3	16.0	16.6	17.3	18.1	18.8	19.6	20.4	21.3	22.1	23.0	23.9	24.9	25.8
	69	13.7	14.2	14.8	15.4	16.1	16.7	17.4	18.2	18.9	19.7	20.5	21.3	22.2	23.1	24.0	25.0
71		13.7	14.3	14.8	15.6	16.1	16.7	17.6	18.2	19.0	19.7	20.5	21.4	22.3	23.1	24.2	
73				14.2	15.1	15.5	16.0	17.0	17.5	18.3	18.9	19.7	20.6	21.5	22.2	23.4	
75							15.3	16.4	16.8	17.6	18.1	18.9	19.8	20.7	21.3	22.6	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	6.0	6.0	6.0	6.0	6.0	6.0	6.1	6.1	6.1	6.1	6.2	6.2	6.2	6.2	6.3	6.3
	43	6.2	6.2	6.2	6.3	6.3	6.3	6.3	6.3	6.4	6.4	6.4	6.4	6.4	6.5	6.5	6.5
	45	6.5	6.5	6.5	6.5	6.5	6.6	6.6	6.6	6.6	6.6	6.6	6.7	6.7	6.7	6.7	6.8
	47	6.8	6.8	6.8	6.8	6.8	6.8	6.8	6.9	6.9	6.9	6.9	6.9	6.9	7.0	7.0	7.0
	49	7.0	7.0	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.2	7.2	7.2	7.2	7.2	7.3	7.3
	51	7.3	7.3	7.3	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.5	7.5	7.5	7.5	7.5	7.6
	53	7.6	7.6	7.6	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.8	7.8	7.8	7.8	7.8	7.8
	55	7.9	7.9	8.0	8.0	8.0	8.0	8.0	8.0	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.2
	57	8.2	8.3	8.3	8.3	8.3	8.3	8.3	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.5	8.5
	59	8.6	8.6	8.6	8.6	8.6	8.7	8.7	8.7	8.7	8.7	8.7	8.8	8.8	8.8	8.8	8.8
	61	8.9	8.9	9.0	9.0	9.0	9.0	9.0	9.1	9.1	9.1	9.1	9.1	9.1	9.1	9.2	9.2
	63	9.3	9.3	9.3	9.3	9.4	9.4	9.4	9.4	9.4	9.4	9.5	9.5	9.5	9.5	9.5	9.5
	65	9.6	9.7	9.7	9.7	9.7	9.8	9.8	9.8	9.8	9.8	9.9	9.9	9.9	9.9	9.9	9.9
	67	10.0	10.0	10.1	10.1	10.1	10.1	10.2	10.2	10.2	10.2	10.2	10.3	10.3	10.3	10.3	10.3
	69	10.4	10.4	10.5	10.5	10.5	10.6	10.6	10.6	10.6	10.6	10.7	10.7	10.7	10.7	10.7	10.8
71		10.7	10.9	10.9	10.9	11.1	11.0	11.0	11.0	11.0	11.2	11.1	11.1	11.1	11.1	11.3	
73				11.3	11.3	11.6	11.4	11.4	11.4	11.4	11.4	11.7	11.5	11.5	11.5	11.8	
75							11.8	11.8	11.8	11.8	12.2	11.9	11.9	11.9	11.9	12.3	

Moc grzewcza (kW)

Temperatura zasilania	41	25.8	26.7	27.6	28.5	29.5	30.5	31.5	32.5	33.5	35.0	36.0	37.0	38.5	39.5	41.0	42.0
	43	25.6	26.5	27.3	28.3	29.2	30.0	31.0	32.0	33.5	34.5	35.5	36.5	38.0	39.0	40.5	41.5
	45	25.4	26.2	27.1	28.0	28.9	29.9	31.0	32.0	33.0	34.0	35.0	36.0	37.5	38.5	40.0	41.0
	47	25.1	26.0	26.8	27.7	28.6	29.5	30.5	31.5	32.5	33.5	34.5	36.0	37.0	38.0	39.5	40.5
	49	24.9	25.7	26.6	27.4	28.3	29.2	30.0	31.0	32.0	33.0	34.0	35.5	36.5	37.5	39.0	40.0
	51	24.7	25.5	26.3	27.1	28.0	28.9	29.8	31.0	32.0	33.0	34.0	35.0	36.0	37.0	38.0	39.5
	53	24.5	25.3	26.1	26.9	27.7	28.6	29.5	30.5	31.5	32.5	33.5	34.5	35.5	36.5	37.5	39.0
	55	24.3	25.0	25.8	26.6	27.4	28.3	29.2	30.0	31.0	32.0	33.0	34.0	35.0	36.0	37.0	38.5
	57	24.1	24.8	25.6	26.4	27.2	28.0	28.9	29.7	30.5	31.5	32.5	33.5	34.5	35.5	36.5	38.0
	59	23.9	24.6	25.4	26.1	26.9	27.7	28.5	29.4	30.5	31.0	32.0	33.0	34.0	35.0	36.0	37.5
	61	23.8	24.5	25.2	25.9	26.7	27.4	28.3	29.1	30.0	31.0	32.0	32.5	33.5	34.5	35.5	37.0
	63	23.6	24.3	25.0	25.7	26.4	27.2	28.0	28.8	29.6	30.5	31.5	32.5	33.0	34.0	35.0	36.5
	65	23.5	24.1	24.8	25.5	26.2	26.9	27.7	28.5	29.3	30.0	31.0	32.0	33.0	34.0	34.5	36.0
	67	23.4	24.0	24.6	25.3	26.0	26.7	27.4	28.2	29.0	29.8	30.5	31.5	32.5	33.5	34.5	35.5
	69	23.3	23.9	24.5	25.1	25.8	26.5	27.2	27.9	28.7	29.5	30.5	31.0	32.0	33.0	34.0	35.0
71		23.8	24.4	24.9	25.6	26.3	27.0	27.6	28.4	29.2	30.5	30.5	31.5	32.5	33.5	34.5	
73				24.7	25.4	26.1	26.8	27.3	28.1	28.9	30.5	30.0	31.0	32.0	33.0	34.0	
75							26.6	27.0	27.8	28.6	30.5	29.5	30.5	31.5	32.5	33.5	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.3	4.5	4.6	4.8	4.9	5.1	5.2	5.4	5.5	5.7	5.9	6.0	6.2	6.4	6.6	6.7
	43	4.1	4.3	4.4	4.5	4.7	4.8	4.9	5.1	5.3	5.4	5.6	5.7	5.9	6.1	6.3	6.4
	45	3.9	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.0	5.2	5.3	5.4	5.6	5.8	6.0	6.1
	47	3.7	3.9	4.0	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.0	5.2	5.4	5.5	5.7	5.8
	49	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.8	5.0	5.1	5.2	5.4	5.5
	51	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.2	4.3	4.5	4.6	4.7	4.8	4.9	5.1	5.2
	53	3.2	3.3	3.4	3.5	3.6	3.7	3.8	4.0	4.1	4.2	4.3	4.5	4.6	4.7	4.8	5.0
	55	3.1	3.2	3.3	3.4	3.5	3.5	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.4	4.6	4.7
	57	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.3	4.5
	59	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.3
	61	2.7	2.8	2.8	2.9	3.0	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0
	63	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.2	3.3	3.4	3.5	3.6	3.7	3.8
	65	2.5	2.5	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.4	3.5	3.6
	67	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5
	69	2.2	2.3	2.3	2.4	2.5	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.2
71		2.2	2.2	2.3	2.4	2.4	2.5	2.5	2.6	2.7	2.7	2.8	2.8	2.9	3.0	3.1	
73				2.2	2.3	2.3	2.4	2.4	2.5	2.5	2.6	2.6	2.7	2.8	2.9	2.9	
75							2.3	2.3	2.4	2.4	2.5	2.5	2.6	2.7	2.7	2.7	

Temperatura zasilania źródła dolnego

6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21

Moc chłodnicza kW

Temperatura zasilania	41	24.3	25.3	26.4	27.5	28.7	29.8	31.0	32.5	33.5	35.0	36.0	37.5	39.0	40.5	42.0	43.5
	43	23.8	24.8	25.8	26.9	28.0	29.2	30.5	31.5	33.0	34.0	35.5	36.5	38.0	39.5	41.0	42.5
	45	23.2	24.2	25.3	26.3	27.4	28.6	29.7	31.0	32.0	33.5	34.5	36.0	37.5	38.5	40.0	41.5
	47	22.7	23.7	24.7	25.7	26.8	27.9	29.0	30.0	31.5	32.5	34.0	35.0	36.5	38.0	39.0	40.5
	49	22.1	23.1	24.1	25.1	26.2	27.2	28.4	29.5	30.5	32.0	33.0	34.5	35.5	37.0	38.5	39.5
	51	21.5	22.5	23.5	24.5	25.5	26.6	27.7	28.8	29.9	31.0	32.5	33.5	35.0	36.0	37.5	39.0
	53	20.9	21.9	22.8	23.8	24.9	25.9	27.0	28.1	29.2	30.5	31.5	33.0	34.0	35.5	36.5	38.0
	55	20.4	21.3	22.2	23.2	24.2	25.2	26.3	27.3	28.4	29.6	30.5	32.0	33.0	34.5	35.5	37.0
	57	19.7	20.6	21.6	22.5	23.5	24.5	25.5	26.6	27.7	28.8	29.9	31.0	32.5	33.5	34.5	36.0
	59	19.1	20.0	20.9	21.8	22.8	23.8	24.8	25.8	26.9	28.0	29.1	30.0	31.5	32.5	34.0	35.0
	61	18.5	19.3	20.2	21.1	22.1	23.0	24.0	25.0	26.1	27.1	28.2	29.4	30.5	31.5	33.0	34.0
	63	17.8	18.6	19.5	20.4	21.3	22.3	23.2	24.2	25.3	26.3	27.4	28.5	29.6	30.5	32.0	33.0
	65	17.1	17.9	18.8	19.7	20.6	21.5	22.4	23.4	24.4	25.4	26.5	27.5	28.6	29.8	31.0	32.0
	67	16.4	17.2	18.0	18.9	19.8	20.7	21.6	22.6	23.5	24.5	25.6	26.6	27.7	28.8	29.9	31.0
	69	15.7	16.5	17.3	18.1	19.0	19.9	20.8	21.7	22.6	23.6	24.6	25.6	26.7	27.8	28.9	30.0
	71		15.8	16.6	17.3	18.2	19.1	20.0	20.8	21.7	22.7	23.6	24.6	25.7	26.8	27.9	29.0
73				16.5	17.4	18.3	19.2	19.9	20.8	21.8	22.6	23.6	24.7	25.8	26.9	28.0	
75										20.9	21.6	22.6	23.7	24.8	25.9	27.0	

Moc elektryczna (kW/400VAC)

Temperatura zasilania	41	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.0
	43	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4	7.4
	45	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7	7.7
	47	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1
	49	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4	8.4
	51	8.7	8.7	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8	8.8
	53	9.1	9.1	9.1	9.1	9.1	9.1	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
	55	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.6	9.6	9.6	9.6	9.6	9.6	9.6
	57	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	9.9	10.0	10.0	10.0	10.0	10.0	10.0	10.0
	59	10.2	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.3	10.4	10.4	10.4	10.4	10.4	10.4
	61	10.7	10.7	10.7	10.7	10.7	10.7	10.7	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8
	63	11.1	11.1	11.1	11.1	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.2	11.3	11.3	11.3	11.3
	65	11.5	11.6	11.6	11.6	11.6	11.6	11.6	11.7	11.7	11.7	11.7	11.7	11.7	11.7	11.7	11.7
	67	12.0	12.0	12.0	12.1	12.1	12.1	12.1	12.1	12.1	12.2	12.2	12.2	12.2	12.2	12.2	12.2
	69	12.5	12.4	12.5	12.5	12.6	12.6	12.6	12.6	12.6	12.6	12.7	12.7	12.7	12.7	12.7	12.7
	71		12.8	13.0	12.9	13.1	13.1	13.1	13.1	13.1	13.0	13.2	13.2	13.2	13.2	13.2	13.2
73				13.3	13.6	13.6	13.6	13.6	13.6	13.4	13.7	13.7	13.7	13.7	13.7	13.7	
75										13.8	14.2	14.2	14.2	14.2	14.2	14.2	

Moc grzewcza (kW)

Temperatura zasilania	41	31.0	32.0	33.0	34.0	35.0	36.5	37.5	38.5	40.0	41.0	42.5	44.0	45.0	46.5	48.0	49.5
	43	30.5	31.5	32.5	33.5	35.0	36.0	37.0	38.5	39.5	41.0	42.0	43.5	44.5	46.0	47.5	49.0
	45	30.5	31.5	32.5	33.5	34.5	35.5	36.5	38.0	39.0	40.5	41.5	43.0	44.0	45.5	47.0	48.5
	47	30.0	31.0	32.0	33.0	34.0	35.5	36.5	37.5	38.5	40.0	41.0	42.5	43.5	45.0	46.5	48.0
	49	29.8	31.0	32.0	33.0	34.0	35.0	36.0	37.0	38.5	39.5	40.5	42.0	43.5	44.5	46.0	47.5
	51	29.6	30.5	31.5	32.5	33.5	34.5	35.5	37.0	38.0	39.0	40.5	41.5	43.0	44.0	45.5	46.5
	53	29.3	30.0	31.0	32.0	33.0	34.5	35.5	36.5	37.5	38.5	40.0	41.0	42.5	43.5	45.0	46.0
	55	29.1	30.0	31.0	32.0	33.0	34.0	35.0	36.0	37.0	38.5	39.5	40.5	42.0	43.0	44.5	45.5
	57	28.8	29.7	30.5	31.5	32.5	33.5	34.5	35.5	36.5	38.0	39.0	40.0	41.5	42.5	44.0	45.0
	59	28.6	29.5	30.5	31.5	32.5	33.5	34.5	35.5	36.5	37.5	38.5	39.5	41.0	42.0	43.0	44.5
	61	28.3	29.2	30.0	31.0	32.0	33.0	34.0	35.0	36.0	37.0	38.0	39.0	40.5	41.5	42.5	44.0
	63	28.1	28.9	29.8	30.5	31.5	32.5	33.5	34.5	35.5	36.5	37.5	38.5	40.0	41.0	42.0	43.5
	65	27.8	28.6	29.5	30.5	31.5	32.0	33.0	34.0	35.0	36.0	37.0	38.5	39.5	40.5	41.5	43.0
	67	27.5	28.3	29.2	30.0	31.0	32.0	33.0	33.5	34.5	35.7	36.5	38.0	39.0	40.0	41.0	42.0
	69	27.2	28.0	28.9	29.7	30.5	31.5	32.5	33.2	34.3	35.3	36.3	37.5	38.5	39.5	40.5	41.5
	71		27.7	28.6	29.4	30.0	31.0	32.0	33.0	34.0	35.0	36.0	37.0	38.0	39.0	40.0	41.0
73				29.1	29.5	30.5	31.5	32.5	33.8	34.7	35.8	36.5	37.5	38.5	39.5	40.5	
75										34.5	35.5	36.0	37.0	38.0	39.0	40.0	

Współczynnik sprawności (COP)

Temperatura zasilania	41	4.4	4.5	4.7	4.8	4.9	5.1	5.3	5.4	5.6	5.8	6.0	6.2	6.4	6.6	6.8	7.1
	43	4.1	4.3	4.4	4.5	4.7	4.9	5.0	5.2	5.3	5.5	5.7	5.9	6.0	6.3	6.5	6.7
	45	4.0	4.1	4.2	4.4	4.5	4.6	4.7	4.9	5.1	5.3	5.4	5.6	5.7	5.9	6.1	6.3
	47	3.7	3.9	4.0	4.1	4.2	4.4	4.5	4.7	4.8	5.0	5.1	5.3	5.4	5.6	5.8	6.0
	49	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.4	4.6	4.7	4.8	5.0	5.2	5.3	5.5	5.7
	51	3.4	3.5	3.6	3.7	3.8	3.9	4.1	4.2	4.3	4.5	4.6	4.7	4.9	5.0	5.2	5.3
	53	3.2	3.3	3.4	3.5	3.6	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.6	4.8	4.9	5.0
	55	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.2	4.4	4.5	4.7	4.8
	57	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	4.2	4.3	4.4	4.5
	59	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.5	3.6	3.7	3.8	3.9	4.0	4.1	4.3
	61	2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.2	3.3	3.4	3.5	3.6	3.8	3.8	3.9	4.1
	63	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.4	3.5	3.6	3.7	3.9
	65	2.4	2.5	2.5	2.6	2.7	2.8	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7
	67	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	2.9	3.0	3.1	3.2	3.3	3.4	3.4
	69	2.2	2.3	2.3	2.4	2.4	2.5	2.6	2.6	2.7	2.8	2.9	3.0	3.0	3.1	3.2	3.3
	71		2.2	2.2	2.3	2.3	2.4	2.4	2.5	2.6	2.7	2.7	2.8	2.9	3.0	3.0	3.1
73				2.2	2.2	2.2	2.3	2.4	2.5	2.6	2.6	2.7	2.7	2.8	2.9	3.0	
75										2.5	2.5	2.5	2.6	2.7	2.8	2.8	